



---

# Lexmark CS730de

Colour and performance

---



# Lexmark CS730de

Designed for security, ease of use, and sustainability, the Lexmark CS730de delivers professional colour for mid-to-large workgroups at speeds up to 40 pages per minute\*. The 10.9 cm tablet-like touchscreen makes completing your printing tasks intuitively easy. Replacement cartridges with Unison™ Toner yield up to 22,000/10,500 black/colour pages\*\* to keep you going.

## Robust, enduring quality

- ▶ Enjoy high-quality colour output in a wide variety of environments - from back-office to retail to harsh manufacturing conditions.
- ▶ Intentionally engineered to last seven years or more with durable steel frames and long-life components.
- ▶ Unison™ Toner replacement cartridges yield up to 22,000/10,500 black/colour pages\*\*.



## Always easy. Always intuitive.

- ▶ Powerful features are easy to use.
- ▶ Large, tablet-like, button-free touchscreens help you intuitively complete every task, from the basic to the complex.
- ▶ Add Lexmark or third-party apps to meet your specific business needs.

## Make a statement with professional colour

- ▶ Enjoy the benefits of vibrant, professional-quality output allowing you to do more colour printing in-house - saves time and money.

- ▶ Match corporate colours on marketing collateral and brand-sensitive text and graphics with PANTONE® calibration and Lexmark Named Colour Replacement.

## Secure by design

- ▶ Lexmark security features help keep your information safe - in the document, on the device, over the network and at all points in between.
- ▶ Always improving security, we now include a standard Trusted Platform Module\*\*\*, which delivers authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint.

## Sustainability matters

- ▶ Designed for the circular economy.
- ▶ Automatic two-sided printing is standard, along with built-in energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- ▶ The award-winning Lexmark Cartridge Collection Programme (LCCP) and Lexmark Equipment Collection Programme (LECP) minimise waste and support recycling (availability varies by country).

## Power up with IoT

- ▶ Our sophisticated, IoT-enabled printers are loaded with sensors that continuously monitor hundreds of data points.
- ▶ When you connect your device to Lexmark Cloud Services, you can optimise performance and uptime with additional features like predictive service and automatic supplies replenishment.


This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

\* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\* Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See [www.lexmark.com/yields](http://www.lexmark.com/yields) for more information. Yield stated on cartridge labels, packaging, and printer device menu pages may be substantially lower than final ISO tested yield. For Lexmark's official statement of yield, see ISO yield reports at [https://www.lexmark.com/en\\_us/products/supplies-and-accessories/iso-page-yields/color-laser-reports.html](https://www.lexmark.com/en_us/products/supplies-and-accessories/iso-page-yields/color-laser-reports.html). Update firmware on your device to ensure accuracy of displayed yield. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Programme (LCCP).

\*\*\* The Trusted Platform Module (TPM) is not available in some countries.

# Lexmark CS730de



- 1 **Printer with 10.9 cm touch screen**  
413 x 479 x 489 mm
- 2 **550-Sheet tray with 100-sheet multipurpose feeder**  
Dimensions included as part of base model
- 3 **550-Sheet Tray**  
119 x 463 x 483 mm
- 4 **550-Sheet Tray**  
119 x 463 x 483 mm

- 5 **550-Sheet Tray**  
119 x 463 x 483 mm
- 6 **550-Sheet Tray**  
119 x 463 x 483 mm
- 7 **Adjustable Stand**  
521 x 653 x 625 mm

- Standard
- Optional

**P/N** 47C9067 **Hardware** Lexmark CS730de

**P/N** 71C0H10 **Supplies** Lexmark CS730, 735, CX730 Black 22K Toner Cartridge

71C0H20 Lexmark CS/CX730 Cyan 10.5K Toner Cartridge

71C0H30 Lexmark CS/CX730 Magenta 10.5K Toner Cartridge

71C0H40 Lexmark CS/CX730 Yellow 10.5K Toner Cartridge

71C0W00 Lexmark CS/CX730, 735, C/XC4342, C4352 170K Waste Container

71C0Z10 Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Black 150K Imaging Unit

71C0Z50 Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Colour (CMY) 150K Imaging Unit

71C10C0 Lexmark CS/CX730, 735 Cyan Return Programme 5K Toner Cartridge

71C10K0 Lexmark CS/CX730, 735 Black Return Programme 5K Toner Cartridge

71C10M0 Lexmark CS/CX730, 735 Magenta Return Programme 5K Toner Cartridge

71C10Y0 Lexmark CS/CX730, 735 Yellow Return Programme 5K Toner Cartridge

71C1HC0 Lexmark CS/CX730 Cyan Return Programme 10.5K Toner Cartridge

71C1HK0 Lexmark CS730, 735, CX730 Black Return Programme 22K Toner Cartridge

71C1HM0 Lexmark CS/CX730 Magenta Return Programme 10.5K Toner Cartridge

71C1HY0 Lexmark CS/CX730 Yellow Return Programme 10.5K Toner Cartridge

**P/N** 40C2100 **Paper Handling** 550-Sheet Tray

**P/N** 27X0400 **Memory Options** 500+ GB Hard Disk

57X0070 Removable Hard Disk Enclosure Kit

57X9528 Intelligent Storage Drive (ISD)

**P/N** 57X0300 **Application Solutions** Contact Authentication Device

57X0301 Contactless Authentication Device

82S1203 IPDS License

82S1204 Bar Code License

**P/N** 1021294 **Connectivity** USB (2 Metre) Cable

27X0823 MarkNet N8370 Wireless for CS720, CS725, CX725

27X6410 Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server

SPD0002 Surge Protective Device, 220-240V

**P/N** 40C2300 **Furniture** Adjustable Stand

## Product Specifications

## Lexmark CS730de

Printing	
Display	Lexmark e-Task 10.9 cm colour touch screen with audible feedback
Print Speed	Up to: Black: 40 ppm <sup>1</sup> (A4) / Colour: 40 ppm <sup>1</sup> (A4)
Time to First Page	as fast as: Black: 6.4 seconds / Colour: 7.0 seconds
Print Resolution	Black: 1200 x 1200 dpi, 4800 Colour Quality (2400 x 600 dpi) / Colour: 4800 CQ (2400 x 600 dpi), 1200 x 1200 dpi
Memory	Standard: 1024 MB / Maximum: 1024 MB
Hard Disk	Intelligent Storage Drive available; Magnetic Hard Disk available
Recommended Monthly Page Volume	1500 - 15000 pages <sup>2</sup>
Maximum Monthly Duty Cycle	Up to: 120000 pages per month <sup>3</sup>
Supplies <sup>4</sup>	
Laser Cartridge Yields	up to: 10,500 <sup>5</sup> -page Colour (CMY) High Yield Cartridges / up to: 22,000 <sup>5</sup> -page Black High Yield Cartridge
Imaging Unit Estimated Yield	Up to: 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage <sup>6</sup>
Cartridge(s) Shipping with Product	5,000 <sup>5</sup> -page Black and Colour (CMYK) Return Programme Toner Cartridges
Paper Handling	
Included Paper Handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 300-Sheet Output Bin, 550-Sheet Input
Optional Paper Handling	550-Sheet Tray
Paper Input Capacity	Up to: Standard: 650 pages 75 gsm bond / Maximum: 2850 pages 75 gsm bond
Paper Output Capacity	Up to: Standard: 300 pages 75 gsm bond / Maximum: 300 pages 75 gsm bond
Media Types Supported	Vinyl Labels, Banner Paper, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope
General Information <sup>7</sup>	
Standard Ports	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB port Compatible with USB 2.0 Specification (Type A), USB 2.0 Specification Hi-Speed Certified (Type B), One Internal Card Slot
Optional Network Ports	Internal MarkNet N8370 802.11b/g/n/a Wireless, NFC
Noise Level	Operating: 52 dBA (Print)
Specified Operating Environment	Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 metres / Humidity: 15 to 80% Relative Humidity
Product Warranty	1-Year Onsite Repair, Next Business Day
Size / Weight	H x W x D: 413 x 479 x 489 mm / 32 kg
ENERGY STAR Typical Electricity Consumption	TEC: 0.53 kilowatt-hours per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

<sup>1</sup> Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details. <sup>5</sup> Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. Yield stated on cartridge labels, packaging and printer device menu pages may be substantially lower than final ISO tested yield. For Lexmark's official statement of yield, see ISO yield reports at [https://www.lexmark.com/en\\_us/products/supplies-and-accessories/iso-page-yields/color-laser-reports.html](https://www.lexmark.com/en_us/products/supplies-and-accessories/iso-page-yields/color-laser-reports.html). Update firmware on your device to ensure accuracy of displayed yield. <sup>6</sup> Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. <sup>7</sup> Printers are sold subject to certain license/agreement conditions. See [www.lexmark.com/printerlicense](http://www.lexmark.com/printerlicense) for details.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2022 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. MOPRIA®, the Mopria® Logo, and the Mopria Alliance™ word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark of the Green Electronics Council in the United States and other countries. PANTONE® is the property of Pantone LLC. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).



[lexmark.com.au](http://lexmark.com.au)