# HP Color LaserJet Enterprise M751 Printer series



# Count on productivity, premium quality, maximum uptime, and the strongest security<sup>1</sup>

HP LaserJet printers power office productivity with a smart, streamlined design that's reliable and hassle-free. Count on premium quality, maximum uptime, and the strongest security<sup>1</sup>—all intended to drive successful organizations forward.



HP Color LaserJet Enterprise M751n



HP Color LaserJet Enterprise M751dn

# Professional color printing

- Print premium, professional-quality documents with vivid color images and graphics.
- Special print mode for a wider color range, an extra level of vividness for documents and marketing materials.
- Consistent professional quality and performance Original HP Toner cartridges with JetIntelligence and drums.
- Look professional on every page with vibrant, high-quality color prints that stand the test
  of time

# Minimal interruptions. Maximum productivity.

- Change the toner and drum in seconds. Both are easily accessible and come already installed out of the box.
- Avoid interruptions with an HP LaserJet printer designed for maximum productivity.
- Tailor this printer to meet the needs of your business with a wide range of paper-handling accessories.
- Grab pages and go, without waiting. This HP LaserJet wakes up quickly and prints fast up to 40 ppm.<sup>2</sup>

# The world's most secure printing<sup>1</sup>

- Each printer in your fleet checks its operating code and repairs itself from attacks.
- Your printer's outgoing network connections are inspected to stop suspicious requests and thwart malware.
- Memory activity is monitored to continually detect and stop attacks
- Firmware is automatically checked during startup to determine if it's authentic code digitally signed by HP.

# Product walkaround



Series at a glance		
	<b>(D)</b>	<b>()</b>
Model (product number)	M751n (T3U43A)	M751dn (T3U44A)
	אכדיטבו) ווו ( וייי	IN STUIT(13044A)
Print speed (A4, black and colour) <sup>4</sup>	Up to 41 pages per minute (ppm) <i>(both models)</i>	
Media sizes supported	Multipurpose tray 1: Up to 305 x 457 mm and SRA3 Tray 2: Up to A3	
Automatic two-sided printing	Not available	✓
100-sheet multipurpose tray 1, 550-sheet tray 2	<b>✓</b>	✓
Optional input accessories  Add up to two: 1x550-sheet paper tray;  Add up to one: 2x550-sheet paper tray and stand, 2,700-sheet high-capacity input paper tray and stand, or Cabinet stand	✓	✓
Input capacity (standard/maximum <sup>5</sup> )	Up to 650 sheets/4,450 sheets (both models)	
Recommended monthly page volume <sup>6</sup>	Up to 40,000 pages (both models)	
Cartridge yields <sup>7</sup> (A/X)	Black: ~7,000/33,000 pages; Colour: ~6,000/28,000 pages (both models)	
Optional HP High-Performance Secure Hard Disk	<b>✓</b>	✓
Optional wireless networking <sup>8</sup> /NFC touch-to-print/Bluetooth <sup>®</sup> Low Energy <sup>9</sup>	<b>✓</b>	<b>√</b>

<sup>&</sup>lt;sup>1</sup> Automatic two-sided printing is not available on the HP Color LaserJet Enterprise M751n model.

<sup>&</sup>lt;sup>2</sup> Solutions deployed through the Hardware Integration Pocket (HIP) may require additional purchase. The HP Color Laser Jet Enterprise M751 series comes with a second-generation HIP.

<sup>&</sup>lt;sup>3</sup> An administrator must enable the easy-access USB port before use.

A Measured using ISO/IEC 24734, excludes first set of test documents. For more information, see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

 $<sup>^{5}</sup>$  Selection of optional paper-handling accessories required to reach maximum input capacity.

<sup>&</sup>lt;sup>6</sup> Recommended Monthly Page Volume (RMPV): HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.

Average black declared yields based on ISO/IEC 19752 and continuous printing. Average colour composite (C/M/Y) declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see hp.com/go/learnaboutsupplies.

Both models can add wireless networking with selection of the optional HP Jetdirect 2900nw Print Server (J8031A). If selected, you cannot also select the HP Jetdirect 3100w BLE/NFC/Wireless Accessory (3JN69A).

Wireless performance is dependent on physical environment and distance from access point and may be limited during active VPN connections

<sup>&</sup>lt;sup>9</sup> Bluetooth and touch-to-print capabilities are optional for both models and can be added by selecting the optional HP Jetdirect 3100w BLE/NFC/Wireless Accessory (3JN69A). If selected, you cannot also select the HP Jetdirect 2900nw Print Server (J8031A). Mobile device must support Near-Field Communication (NFC)-enabled printing. For more information, see hp.com/go/businessmobileprinting.

## **HP Services**

Downtime can have serious consequences, so HP provides support beyond the standard warranty. You benefit from reduced risk, maximized uptime, predictable service delivery and no unbudgeted repair costs.

Choose from:

# Optimized Care (optimum performance and stability):

4 hour Onsite Support, Maintenance Kit Replacement Service, Installation with Network Configuration

#### Standard Care (high level of uptime):

Next Business Day Onsite Support, Maintenance Kit Replacement Service, Installation with Network Configuration Service

## Basic Care (minimum recommended support):

Next Business Day Onsite Support

#### 4 hour Onsite Support:

Onsite support within four hours after a service call received within the coverage window

### Next Business Day Onsite Support:

Onsite service the next business day after the service call is received

#### Maintenance Kit Replacement Service:

Onsite replacement of your printer's maintenance kit including parts, materials, and labor

# Installation with Network Configuration Service:

Assembly, network configuration, and basic administrator familiarization. For more information about HP Care Pack, HP Contractual, or HP Managed Print Services, visit hp.com/go/printservices



















# Top features

Expect premium marketing materials and professional-quality documents with vivid color images and graphics. Built for great color performance with an enhanced print mode and a toner formula designed for consistent quality and brilliant color output.

Annoying interruptions and complex maintenance can slow down printing and the pace of business. Avoid pauses in productivity with an HP LaserJet Printer designed for maximum uptime, so you can count on reliable results day in and day out.

HP printers have the industry's strongest security 1 because they're always on guard, continually detecting and stopping threats while adapting to new ones. And only HP printers automatically self-heal from attacks, so IT doesn't need to intervene.

#### Product

T3U43A HP Color LaserJet Enterprise M751n T3U44A HP Color LaserJet Enterprise M751dn

#### Accessories

3JN69A HP Jetdirect 3100w BLE/NFC/Wireless Accessory
 B5L28A HP Internal USB Ports
 B5L29A HP High-Performance Secure Hard Disk
 B5L31A HP Foreign Interface Harness
 E5K48A HP 1 GB x32 144-pin (800 MHz)DDR3 SODIMM

E5K49A HP 2 GB x32 144-pin (800 MHz) DDR3 SODIMM

J8031A HP Jetdirect 2900nw Print Server

T3V27A HP LaserJet 550-sheet Paper Tray

T3V28A HP LaserJet Printer Stand
T3V29A HP Color LaserJet 2x550-sheet Feeder and Stand

T3V30A HP LaserJet 2700-sheet High Capacity Paper Tray and Stand
X3D03A HP Universal USB Proximity Card Reader

### Supplies

W2000A HP 658A Black Original LaserJet Toner Cartridge (7,000 pages) W2000X HP 658X High Yield Black Original LaserJet Toner Cartridge (33,000 pages) W2001A HP 658A Cyan Original LaserJet Toner Cartridge (6,000 pages) W2001X HP 658X High Yield Cyan Original LaserJet Toner Cartridge (28,000 pages) W2002A HP 658A Yellow Original LaserJet Toner Cartridge (6,000 pages) W2002X HP 658X High Yield Yellow Original LaserJet Toner Cartridge (28,000 pages) W2003A HP 658A Magenta Original LaserJet Toner Cartridge (6,000 pages) W2003X HP 658X High Yield Magenta Original LaserJet Toner Cartridge (28,000 pages) W2004A HP 660A Original LaserJet Imaging Drum (65,000 pages)

# **HP Care Packs**

UB5C3E HP 3 year Next Business Day w/DMR Service for Color LaserJet M751
UB5C4E HP 4 year Next Business Day w/DMR Service for Color LaserJet M751
UB5C5E HP 5 year Next Business Day w/DMR Service for Color LaserJet M751
UB5C6E HP 3 year 4 hour 9x5 w/DMR Service for Color LaserJet M751
UB5C7E HP 4 year 4 hour 9x5 w/DMR Service for Color LaserJet M751
UB5C8E HP 5 year 4 hour 9x5 w/DMR Service for Color LaserJet M751

Protect your investment with HP Care Pack. Let HP certified engineers resolve your technical issues. For more details on HP Care Pack, go to hp.com/go/cpc

#### Paper

Contact HP via phone: Asia: 65 6253 8500

# Solutions

HP Web Jetadmin: hp.com/go/wja

HP Universal Print Driver: hp.com/go/upd
HP Imaging and Printing Security Center: hp.com/go/ipsc

# HP Color LaserJet Enterprise M751 Printer series

Productions Protections Protec	Model	HP Color LaserJet Enterprise M751n	HP Color LaserJet Enterprise M751dn	
Piete  The property incloses  Bod MM, normal place provised  Bod MM, normal place provised				
Discreption of the control of their support provided (and their support provided) (and their support provided) (but the control of the control of their support provided) (but the control of the control			הדייטכו	
Amount of teachers   Amount of their as support provided		T THIL		
Basic After Town Live 1 or 1 proc Basic (later command): 10 or 10 proc Basic (later duplement) to 16 proc Basic (later town Live 1		Manual (driver support provided)	Automatic (standard)	
Back My, mady, fire facts as 57 acc. Colour LMA, ready, fire facts as 51 acc. Colour LMA, seeph fire facts as 51 acc. Colour		Black (A4, normal): Up to 41 ppm; Black (letter, normal): Up to 40 ppm; Black (A4, duplex): Up to 41 ipm; Black (letter, duplex): Up to 40 ipm		
Description	Eirct page out <sup>17</sup>			
Print residuation   Geode Reset) (a) 16 601 x 5000 at 18 deck from 20 to 10 x 5000 at 18 deck from 18 to 10 x 5000 at 10			st as 11.5 sec, <b>coloui (1-1, sieep).</b> As last as 11.5 sec	
Pilet cardidges  4 terre cartridges (1 each for block, own magents, pellow)  Pilet cardidges  4 terre cartridges (1 each for block, own magents, pellow)  Pilet cardidges  4 terre cartridges (1 each for block, own magents, pellow)  Pilet cardidges  4 terre cartridges (1 each for block, own magents, pellow)  Pilet cardidges  4 terre cartridges (1 each for block, own magents, pellow)  Pilet cardidges  4 terre cartridges (1 each for block, own magents, pellow)  Pilet cardidges  Pilet cardidges  4 terre cartridges (1 each for block)  Pilet cardidges		Black (best) Up to 600 x 600 dpi; Black (normal) Up to 600 x 600 dpi; Black (fine lines) Up to 1200 x 1200 dpi		
## PPCE, # IPPC   Sept 10 of 100, 150 of 1				
Impulses   Professional Comment		4 toner cartridges (1 each for black, cyan, magenta, yellow)		
The connectivity of the control of t		HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.4), Apple AirPrint™		
Sandard connectivity  3. His Speed Device USB 2.0, 24 His Speed USB 2.0 near host ports, 1 walkup USB 2.0 host port, 1 Gigabil/Fast Ethernet 10/100/1000 Base-TX network port; 1 Hardware Integration Pocket 2nd generation Flight Park (page Winters ** Morphin* Certified, Coopie Gloud Print***, 14 Peans capability  1. Weeless apability  1. Weeless apability  1. Wes (Sa Pa) Parkenet Ethernet infectioder port server (standard) supports (100 USB Wineless Pint Server 180/26)  1. Weeless apability  1. Wes (Sa Pa) Parkenet Ethernet infectioder port server (standard) supports (100 USB Wineless Pint Server 180/26)  1. Weeless (100 Morphin****)  1. Ves (Sa Pa) Parkenet Ethernet infectioder port server (standard) supports (100 USB Wineless Pint Server 180/26)  1. Weeless (100 Morphin**)  1. Ves (Sa Pa) Parkenet Ethernet infectioder port server (standard) supports (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Parkenet Ethernet infectioder port server (standard) supports (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Parkenet Ethernet and Gig Links; Pasc (standard)  1. Ves (Sa Pa) Parkenet Ethernet and Gig Links; Pasc (standard)  1. Ves (Sa Pa) Parkenet Ethernet and Gig Links; Pasc (standard)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180/26)  1. Ves (Sa Pa) Pasce (100 USB Wineless Pint Server 180	Printer management	HP Printer Assistant; HP Utility (Mad); HP Device Toolbox; HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator)		
Mobile printing (periation (HIP2)  Whe Phinting Application Printing Mooraal** (Certifiedt, Google Cloud Printing**) He Popers (Application)  Whe Popers (Application)  Standard 1.5 (16) Memory 2.0 Householder (International Control of Printing**) He Popers (Application)  Standard 1.5 (16) Memory 2.0 Householder (International Control of Printing**) He Popers (Application)  Standard 1.5 (16) Memory 2.0 Householder (International Control of Printing**) He Popers (International Control of Printing**) He Pope	Connectivity			
Copposition	Standard connectivity	1 Hi-Speed Device USB 2.0; 2 Hi-Speed USB 2.0 rear host ports; 1 walkup USB 2.0 host port; 1 Gigabit/Fast Ethernet 10/100/1000 Base-TX network port; 1 Hardware Integration Pocket 2nd generation (HIP2)		
Nework capabilities  New Value Pf defined. Ethernet embedded print sever (standard) supports: 108ase-Tx, 1008ase-Tx, 1008ase-T	capability			
Memory   Sandard: 1, 66 Meximum 2 (8)   Memory   Sandard: 1, 66 Memory   Sandard: 1,	Wireless capability			
Processor speed 1.2 (2 Hz Duty cycle (monthly)) <sup>13</sup> Processor speed 1.2 (2 Hz Duty cycle (monthly)) <sup>13</sup> Pub (150,000 pages, Recommended monthly page volume) <sup>14</sup> , Up to 40,000 Pager handling Processor speed		802.11b/g/n wireless networking (optional)		
Processor speed  Duty cycle (monthly) <sup>13</sup> Duty 150,000 pages, Recommended monthly page volume <sup>14</sup> -Up to 40,000  Pager handling  Input  100-sheet multipurpose tray, \$50-sheet input tray  250-sheet output bin  Redia veight  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Tray 3,4,5,6 do to 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Tray 3,4,5,6 do to 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Tray 3,4,5,6 do to 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 250 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 127 to 250 at 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m²  Tray 1: 60 at 250 g/m² Optional Holl Feeder stand; 60 to 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m² Optional Holl Feeder stand; 60 to 256 g/m² Optional Holl Feeder				
Duty to 150.000 pages; Recommended monthly page volume <sup>14</sup> ; Up to 40,000 Pager handling  The Pager handling  100-sheet multipurpose tray, 550-sheet input tray  201-sheet output bin  205-sheet output bin  206-sheet sheet, 60 to 256 g/m²  206-sheet output bin  206-sheet sheet, 61 bin 200 g/m², Tray 2.6 bin 256 g/m², Optional Tray 3.4, 5, 6:148 x 148 to 250 x 457.2 mm  206-sheet sheet bin 206 g/m²  206-sheet sheet, 62 bin 256 g/m²  207-sheet sheet, 62 bin 256 g/m²  207-shee	Hard disk	Optional 500 GB HDD: HP Secure High Performance Hard Disk drive 500 GB B5L29A; HP FIPS-140-2 Secure Hard Disk Drive 5EL03A		
Input 100-sheet multipurpose tray, 550-sheet input tray 250-sheet input tray 250-sheet output bin 250-sheet	Processor speed			
Duput   100-sheet multipurpose tray, 550-sheet input tray   255-sheet output bin   255-sh	Duty cycle (monthly) <sup>13</sup>	Up to 150,000 pages; <b>Recommended monthly page volume<sup>14</sup>:</b> Up to 40,000		
Security managements   250-sheet output bin   250-sheet output   250-sheet output bin   2	Paper handling			
Media vesight Tray 1: 60 to 300 g/m², Tray 2: 60 to 256 g/m², Optional HOL Feeder stand: 60 to 256 g/m² Media Sizes Custom Tray 1: 60 to 300 g/m², Tray 2: 60 to 256 g/m², Optional HOL Feeder stand: 60 to 256 g/m² Media Sizes Custom Tray 1: 60 to 300 g/m², Tray 2: 60 to 256 g/m², Optional HOL Feeder stand: 60 to 256 g/m² Media Sizes Custom Tray 1: 60 to 300 g/m², Tray 2: 748 x 148 to 297 x 431.8 mm; Optional tray 3, 4, 5, 6: 148 x 148 to 320 x 457.2 mm Tray 1: 60 to 300 g/m², Tray 2: 748 x 148 to 297 x 431.8 mm; Optional tray 3, 4, 5, 6: 148 x 148 to 320 x 457.2 mm  Meght 45.1 kg Whats in the box¹ HP Color Laser let Enterprise M751 n printer; (1 each, Black, Cyan, Yellow, Magental); Documentation only, CD, Guide: Getting started Guide; 1 Power cord Documentation only, CD, Guide: Getting started Guide; 1 Power cord Documentation only, CD, Guide: Getting started Guide; 1 Power cord Documentation only, CD, Guide: Getting started Guide; 1 Power cord Documentation only, CD, Guide: Getting started Guide; 1 Power cord Documentation only, CD, Guide: Getting started Guide; 1 Power cord Documentation only, CD, Guide: Getting started Guide; 1 Power cord Documentation only, CD, Guide: Getting started Guide; 1 Power cord Documentation only, CD, Guide: Getting started Guide; 1 Power cord Documentation only, CD, Guide: Getting started Guide; 1 Power cord Documentation only, CD, Guide: Getting started Guide; 1 Power cord One-year, next-business day, onsite warranty, Warranty and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to hp.com/suport to learn about HP avendor with the support options in your respon. Warranty, Code 4G, Warra	Input	100-sheet multipurpose tray, 550-sheet input tray		
Media Sizes Custom Tray 1: 60 to 300 g/m²; Tray 2: 60 to 256 g/m²; Optional Hot feeder stand; 60 to 256 g/m² Media Sizes Custom Tray 1: 64 x 127 to 320 x 457.2 mm; Tray 2: 148 x 148 to 297 x 431.8 mm; Optional tray 3, 4, 5, 6: 148 x 148 to 320 x 457.2 mm  Dignerisons (w x d x ) Software Solutions are included in the Box, only on http://px.com, http://rz.ahp.com; Documentation only, CD; Guide: Getting started Guide; Plower cord Documentation only, CD; Guide: Getting started Guide; Plower cord Documentation only, CD; Guide: Getting started Guide; Plower cord Documentation only, CD; Guide: Getting started Guide; Plower cord Documentation only, CD; Guide: Getting started Guide; Plower cord Documentation only, CD; Guide: Getting started Guide; Plower cord One-year next-business day, onsite warranty, Warranty and support options way by product, country and local legal requirements. Contact your Contractual Vendor or go to hp.com/support to learn about HP award winning service and support options in your region. (Warranty Code 4G; Warranty ID A001) Windows Glient OS (32/64 bit), Windows A, Apple® macOS Sierr vol 10.12, Apple® macOS Sierr vol 10.12, Apple® macOS Migrave Vol 10.14, Disrete PCL6 Printee Priver, For more information on the supported operating systems go to http://support.hp.com, Enter your product name and search, Click on User Guides and enter your product name and search for User Guide, Search for the Supported Operating Systems see www.hp.com/gol/guid Minimum system requirements  Pock Ga available hard drive space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com;  Mac 2 Ga available hard drive space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see microsoft.com;  Mac 2 Ga available hard drive space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see applic.com;  Mac 2 Ga available hard drive space, Internet connection or USB port, Internet browser. Provin	Output			
Tray 1: 64 x 127 to 320 x 457.2 mm; Tray 2: 148 x 148 to 297 x 431.8 mm; Optional tray 3, 4, 5, 6: 148 x 148 to 320 x 457.2 mm   Dignersions (w x d x   Variety of the control of the co	Media types	Paper (plain, heavy, extra heavy, glossy, light, recycle, tough), envelopes, labels, glossy film, cardstock, transparencies		
Weight   What's in the box   White   What's in the box   HP Color Laser let Enterprise M751n printer; (1 each, Black, Cyan, Yellow, Magenta);   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power cord   Documentation only CD; Guide: Getting started Guide; 1 Power CD; Documentation only CD; Guide: Getting started Guide; 1 Power CD; Documentation only CD; Guide: Getting started Guide; 1 Power CD; Documentation only CD; Guide: Getting started Guide; 1 Power CD; Documentation only CD; Guide: Getting started Guide; 1 Power CD; Documentation only CD; Guide: Getting started Guide; 1 Power CD; Documentation only CD; Guide: Getting started Guide; 1 Power CD; Documentation only CD; Guide: Getting started Guide; 1 Power CD; Documentation CD; Documentation only CD; Guide: Getting started Guide; 1 Power CD; Documentation C	Media weight			
Weight 45.1 kg What's in the box¹		Tray 1: 64 x 127 to 320 x 457.2 mm; Tray 2: 148 x 148 to 297 x 431.8 mm; Optional tray 3, 4, 5, 6: 148 x 148 to 320 x 457.2 mm		
What's in the box 1  Documentation only CD, Guide: Getting started Guide; 1 Power cord  No software included  No software solutions are included in the Box, only on http://hp.com, http://hp.com;  One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to hp.com/support to learn about HP award winning service and support options in your region. (Warranty) Code 4G; Warranty 10 A001)  Systems  Windows Client OS (32/64 bit), Windows 10, Windows 8, 11, Windows 8 Basic, Windows 8 Pro, Windows 8 Enterprise, Windows 8 Enterprise, Windows 7 Starter Edition SP1, UPD Windows 7 Ultimate, Mobile OS, iOS, Android, Mac, Apple* macOS Sierra v10.12, Apple* macOS High Sierra v10.13, Apple* macOS Mojave v10.14, Discrete PCL6 Printer Driver, For more information on the Supported operating systems go to http://support.hp.com, Enter your product name and search, clk on User Guides and enter your product name and search for User Guide, Search for your Product Name) – User Guide, Search for the Supported Operating Systems Section, UPD PCLG / PS Printer Drivers, Supported Operating Systems, For more information on the supported operating Systems Section, UPD PCLG / PS Printer Drivers, Supported Operating Systems, For more information on the supported operating Systems Section, UPD PCLG / PS Printer Drivers, Supported Operating Systems, For more information on the supported operating Systems Section, UPD PCLG / PS Printer Drivers, Supported Operating Systems, For more information on the supported operating Systems Section, UPD PCLG / PS Printer Drivers, Supported Operating Systems, For more information on the Systems Section, UPD PCLG / PS Printer Drivers, Supported Operating Systems, For more information on the Systems Section, UPD PCLG / PS Printer Drivers, Supported Operating Systems, For more information on the Systems Section, UPD PCLG / PS Printer Drivers, Supported Operating Systems, For more information on the Systems	Dimensions (w x d x h) <sup>10</sup>	556 x 589 x 399 mm		
Documentation only CD; Guide: Getting started Guide; 1 Power cord    Documentation only CD; Guide: Getting started Guide; 1 Power cord	Weight	45.1 kg		
Warranty features  One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to hp.com/support to learn about HP award winning service and support options in your region. (Warranty Code 46; Warranty ID A001)  Systems  Windows Client OS (32/64 bit), Windows 81, Windows 8 B asic, Windows 8 Pro, Windows 8 Enterprise, Windows 8 Enterprise, Nindows 7 Starter Edition SP1, UPD Windows 7 Starter Editi	What's in the box <sup>1</sup>	HP Color LaserJet Enterprise M751n printer; (1 each, Black, Cyan, Yellow, Magenta); Documentation only CD; Guide: Getting started Guide; 1 Power cord	HP Color LaserJet Enterprise M751dn printer; (1 each, Black, Cyan, Yellow, Magenta); Documentation only CD; Guide: Getting started Guide; 1 Power cord	
Learn about HP award winning service and support options in your region. (Warranty Code 4G; Warranty ID A001)	Software included			
Windows Client OS (32/64 bit), Windows 10, Windows 8, 1, Windows 8 Bric, Windows 8 Pro, Windows 8 Enterprise, Windows 8 Enterprise, Nindows 7 Starter Edition SP1, UPD Windows 8 pystems 15 windows 8 Enterprise, Windows 8 E	Warranty features	One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to hp.com/support to learn about HP award winning service and support options in your region. (Warranty Code 4G; Warranty ID A001)		
Ultimate, Mobile QS, iOS, Android, Mac, Apple® macOS Sierra v10.13, Apple® macOS Mojave v10.14, Discrete PCL6 Printer Driver, For more information on the supported operating systems go to http://spuport.hp.com, Enter your product name and search Click on User Guides, search for User Guide, Search for your (Product Name) - User Guides, Search for the Supported Operating Systems see www.hp.com/go/upd  Minimum system requirements  PC:2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com;;  Mac: 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com;  Security management  Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerbero Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in  Tonts and typefaces  Osintrol panel  2.7-in (6.86 cm) QVGA LCD (Color graphics) rotating (adjustable angle) display with 24-key pad  Display  2.7-in (6.86 cm) QVGA LCD (Color graphics) rotating (adjustable angle) display with 24-key pad  Power supply type: Built-in 115V or 220V Power supply: Power supply required: Input voltage: 100 V to 127 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-0%), 50 - 60 Hz nominal (+/-0%), 50 - 60	Systems			
Mac: 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com;   Security management   Mac: 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com;   Security management   Management security: SNMPV3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP-PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerbero Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in	Compatible operating systems <sup>15</sup>	Ultimate, Mobile OS, iOS, Android, Mac, Apple® macOS Sierra v10.12, Apple® macOS High Sierra v10.13, Apple® macOS Mojave v10.14, Discrete PCL6 Printer Driver, For more information on the supported operating systems go to http://support.hp.com, Enter your product name and search, Click on User Guides and enter your product name and search for User Guide, Search for the Supported Operating Systems section, UPD PCL6 / PS Printer Drivers, Supported Operating systems, For more information on the supported Operating		
Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in  Ponts and typefaces  Control panel  105 internal TrueType fronts scalable in HP PCL, 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at hp.com/go/laserjetfonts  Control panel  2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad  2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad  2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad  Power supply type: Built-in 115V or 220 V Power Supply; Power supply:		Mac: 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com;		
Control panel  2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad  2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad  2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad  2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad  Power supply type: Built-in 115V or 220V Power Supply; Power supply required: Input voltage: 100 V to 127 V nominal (+/- 10%), 50 - 60 Hz nominal (+/- 3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/- 10%), 50 - 60 Hz nominal (+/- 3 Hz), 6 A; Power consumption?: 870 watts (max. printing), 850 watts (typical printing) 48 watts (Ready), 0.6 watts (Sleep), 0.6 watts (HP Auto-Off/Auto-Off), 0.0.8 watts (Auto-Off), 0.08 watts (Off); Typical Electricity Consumption number 1: 1.33 kWh/Week (BA), 1.31 kWh/Week (ES)  Acoustics  Acoustic power emissions 12: 6.6 B(A); Acoustic power emissions (ready): 4.5 B(A); Acoustic pressure emissions bystander (ready): 30 dB(A)  Environmental ranges  Operating temperature range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% R  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:22011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:22101/IEC 62479:2210; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/UL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-0 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Supported network  IPV4/IPV6: Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, FTP, FTP, FTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPSec/Firewall; IPV6: DHCPV6, MLDV1,	Security management			
Power supply type: Built-in 115V or 220V Power Supply; Power supply required: Input voltage: 100 V to 127 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-3 Hz), 12 A; Input voltage: 220 V		Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP Laser Jet Fonts and IPDS Emulation available at hp.com/go/laserjetfonts		
Power supply type: Built-in 115V or 220V Power Supply; Power supply required: Input voltage: 100 V to 127 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/-3 Hz), 12 Hz), 60 Hz nominal (+/-3 Hz), 12 Hz), 60 Hz nominal (+/-3 Hz), 12 Hz), 12 Hz, 12 Hz				
nominal (+/-1096), 50 - 60 Hz nominal (+/-3 Hz), 6 A; Power consumption <sup>2</sup> : 870 watts (max. printing), 850 watts (typical printing) 48 watts (Ready), 0.6 watts (Sleep), 0.6 watts (HP Auto-Off)/Auto On), 0.08 watts (Auto-Off), 0.08 watts (Off); Typical Electricity Consumption number <sup>4</sup> : 1.93 kWh/Week (BA), 1.91 kWh/Week (ES)  Acoustic power emissions <sup>12</sup> : 6.6 B(A); Acoustic power emissions (ready): 4.5 B(A); Acoustic pressure emissions bystander (active, printing): 51 dB(A); Acoustic pressure emissions bystander (ready): 30 dB(A)  Environmental ranges  Operating temperature range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% R  Environmental ranges  Operating temperature range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% R  Ecoposition of the control of the contr	Display			
Acoustic power emissions 12: 6.6 B(A); Acoustic power emissions (ready): 4.5 B(A); Acoustic pressure emissions bystander (active, printing): 51 dB(A); Acoustic pressure emissions bystander (ready): 30 dB(A)  Derating temperature range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% R  Environmental ranges  Departing temperature range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% R  Elec 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-0' 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Supported network  IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, FTP, FTP, FTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPsec/Firewall; IPv6: DHCPv6, MLDv1,	Power	Power supply type: Built-in 115V or 220V Power Supply: Power supply required: Input voltage: 100 V to 127 V nominal (+/-10%), 50 - 60 Hz nominal (+/- 3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/- 3 Hz), 6 A; Power consumption <sup>2</sup> : 870 watts (max. printing), 850 watts (typical printing), 48 watts (Ready), 0.6 watts (Sleep), 0.6 watts (HP Auto-Off/Auto On), 0.08 watts (Auto-Off), 0.08 watts (Auto-Off), 100 watts (Word Electricity Consumption number <sup>4</sup> : 1.93 kWh/Week (BN). 1.91 kWh/Week (ES)		
Environmental ranges  Operating temperature range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% R  Safety approvals and requirements  Safety approvals and requirements  Supported network  Supported network  Operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% R  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014 (ICass 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-01 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Supported network  IPV4/IPV6: Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, TFTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPSec/Firewall; IPV6: DHCPV6, MLDv1,	Acoustics	Acoustic power emissions 12: 6.6 B(A); Acoustic power emissions (ready): 4.5 B(A); Acoustic pressure emissions bystander (active, printing): 51 dB(A); Acoustic pressure emissions bystander		
Safety approvals and requirements    IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2	Environmental ranges	a year and a second	Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% RH	
	Safety approvals and requirements	IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.		

#### **Footnotes**

- 1 Based on HP review of 2018 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a reboot. For a list of printers, visit http://hp.com/go/PrintersThatProtect. For more information: http://hp.com/go/printersecurityclaims
- <sup>2</sup> Measured using ISO/IEC 24734, excludes first set of test documents. For more information, see http://hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

#### Technical specifications disclaimers

- 1 Standard cartridges included; yields 7,000 black and 6,000 color composite (C/M/Y) pages. Drums included; yields 65,000 black and color pages. Average black declared yields based on ISO/IEC 19752 and continuous printing. Average color composite (C/M/Y) declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see
- <sup>2</sup> With print cartridges.
- <sup>3</sup> Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption values typicallty based on measurement of 115 V device.
- 4 Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115 V device.
- Based on the BA TEC method with the following possible exceptions: 1 minute or less sleep delay setting, Wi-Fi disabled.
- 6 Average black declared yields based on ISO/IEC 19752 and continuous printing. Average color composite (C/M/Y) declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/go/learnaboutsupplies.
- Average black declared yields based on ISO/IEC 19752 and continuous printing. Average color composite (C/M/Y) declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/go/learnaboutsupplies.

  B The Configuration Pages will report maximum memory at 2 GB after 1 GB DIMM installed. This is an expected behavior of this product.
- <sup>9</sup> With print cartridges.
- 10 Without paper trays extended
- 11 With print cartridges.
- 12 Acoustic values are subject to change. For current information see http://www.hp.com/support. Configuration tested: base model, simplex printing, A4 paper at an average of 41 ppm.
- 13 Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

  14 HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty
- period.

  15 Solution software available on 123.hp.com

# To learn more, visit http://www.hp.com

