HP DeskJet 4100e All-in-One series



Multi-task with ease – easy setup with HP Smart app, worry-free wireless, and ink savings.

All the features. All the value. Built to save time with an automatic document feeder, you'll get a hassle-free experience for printing, scanning, and copying everyday documents, plus faster, more reliable connections.¹ With a simple setup using the HP Smart app, you're ready to go on any device.² Choose HP+ and get 6 months of printing³ and 1 extra year of HP customer support with use of Original HP Ink.





Added extras so you can do more



- Work fast and hands-free—the 35-page auto feeder helps you complete scan and copy jobs quickly.
- Easily print, scan, and copy everyday documents from your smartphone, using HP Smart app.²
- Get better range and faster, more reliable connections using dual-band Wi-Fi® with self-reset.¹
- Get connected with Bluetooth® and start printing fast from your smartphone or tablet easy setup.⁴

Simple setup. Simple printing.



- Get started fast with simple setup that guides you through each step, using HP Smart app.²
- Easily handle tasks and get a lot from one device print, scan, and copy.
- Get quick and easy printing directly at the control panel.
- This printer is made from recycled printers and other electronics—more than 20% by weight of plastic.

Never run out⁸ and save up to 50%⁶ with Instant Ink

- Enroll to Instant Ink to get ink, plus hassle-free delivery and recycling while saving up to 50%. 6
- Change or cancel any time.¹⁰

HP+ Smart printing has arrived



HP AiO Remote

- With HP+, get connected cloud that automatically detects and fixes connectivity issues.⁹
- Never run out of ink⁸ and save up to 50% with Instant Ink⁶. 6-month trial with HP+.³
- With HP+, get advanced HP Smart app solutions such as easy multi-paged documents scanning from your phone.²
- HP+ requires HP account, internet connection, and exclusive use of Original HP Ink cartridges to operate.

This is an HP+ enabled printer. Choose HP+ at product setup to activate benefits. HP+ requires an HP account, ongoing connection to the internet, and exclusive use of Original HP Ink cartridges for the life of the printer. More at: http://www.hp.com/plus-faq. This printer is intended to work only with cartridges that have new or reused HP electronic circuitry, and it uses dynamic security measures to block cartridges using modified or non-HP circuitry. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. Reused HP electronic circuitry enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

Technical specifications

Print speed* Black (MA, normal) Up to 8.5 ppm; Color (A4, normal) Up to 5.5 ppm; Black (A4, draft): Up to 20 ppm; Color (A4, draft): Up to 20 ppm; Color (A4, draft): Up to 20 ppm; Color (A4, draft): Up to 5.5 ppm; Black (A4, draft): Up to 20 ppm; Color (A4, draft): Up to 5.5 ppm; Black (A4, draft): Up to 20 ppm; Color (A4, draft): Up to 5.5 ppm; Black (A4, draft): Up to 20 ppm; Color (A4, draft): Up to 5.5 ppm; Black (A4, draft): Up to 20 ppm; Color (A4, draft): Up to 5.5 ppm; Black (A4, draft): Up to 20 ppm; Color (A4, draft): Up to 5.5 ppm; Black (A4, draft): Up to 4800 x 1200 optimized dip 10 ppm; Color (A4, draft): Up to 20 ppm; Color (A4, draft): Up to 4800 x 1200 optimized dip 10 ppm; Color (A4, draft): Up to 20 ppm; Color (A4, draft): Up to 4800 x 1200 optimized dip 10 ppm; Color (A4, draft): Up to 20 ppm; Color (A4, draft): Up to 4800 x 1200 optimized dip 10 ppm; Color (A4, draft): Up to 20 ppm; Color (Functions	Print, copy, scan, send mobile fax
Bode likes printing Mo State (MA) commail (by to 8 5 ppm, Color (AA) commail (b) to 5.5 ppm, Black (MA), draft?) Up to 20 ppm, Color (AA, draft?) Up to 75 ppm, Colo		тип, сору, зсап, зена тоопе нах
Duples printing Manual (filters support provided) Back (An commail) to 16.5 ppm; Black (And, commail) to 16.5 ppm; Black (And, draft2) Up to 20 ppm; Color (AA, draft2) Up to 16 ppm; Black (AN, draft2) (AR, draft2) Up to 16 ppm; Black (AN, draft2) (AR, draft2) Up to 16 ppm; Black (AN, draft2) (AR, draf		No.
Pirst speed 1 SBack (MA), romablilly to 8.5 spmr. Color (SA), romablilly to 15.5 spmr. Black (AA), draft? Up to 15 ppmr. Color (AA), rotalit? Up to 15 ppmr. Color (AA), rotalit? Up to 15 ppmr. Color (AA), rotalit? Up to 15 ppmr. Color (AA), rotalit. Up to 15 ppmr. Color (AA), rotalit. Up to 15 ppmr. Color (AA), rotalit. ABAC (AA), rotalit. Up to 15 ppmr. Color (AA), rotalit. ABAC (A		
First page out Black (Air, ready). As 618 as 51 Sec. Color (Argan), As 618 as 19 sec. First topic out Black (Air, ready). As 618 as 19 sec. First topic out Black (Air, ready). As 618 as 19 sec. First topic out Black (Air, ready). As 618 as 19 sec. First topic out Black (Air, ready). As 618 as 19 sec. First topic out Black (Air, ready). As 618 as 19 sec. First topic out Black (Air, ready). As 618 as 19 sec. First contridges number 2 10 sec. 2 10 sec. black (Lincold). 2 10 sec. black (Lincold). First carridges number 3 compared by 19 pp. 19	Duplex printing	
Print resolution Print resolution Black (best) Up to 1200X 1200 rendered gir (when Prienting from a computer). Color (best) Up to 4800 x 1200 optimized dip color (when printing from a computer) and the photo papers and 1200 input dipi) Print cartridges number 2 (I asch black, Tre-cold) Standard print languages HP PCL 3 (Lish Plack, Tre-cold) Standard print languages HP PCL 3 (Lish Plack, Tre-cold) Standard print languages HP PCL 3 (Lish Plack, Tre-cold) Standard print languages HP PCL 3 (Lish Plack, Tre-cold) Standard print languages HP PCL 3 (Lish Plack, Tre-cold) Standard print languages HP PCL 3 (Lish Plack, Tre-cold) Standard print languages HP PCL 3 (Lish Plack, Tre-cold) Standard print languages HP PCL 3 (Lish Plack, Tre-cold) Standard print languages HP PCL 3 (Lish Plack, Tre-cold) Standard print languages HP PCL 3 (Lish Plack, Tre-cold) Standard print languages Normal (A4) Up to 2.5 (pm (200po), 1864 Lish 19 to 2.5 (pm (200po), cold) Standard print languages Standard printing from a computer (CS), Stan Input modes From-panel scan, Standard printing from a computer (CS), Stan Input modes From-panel scan, Standard printing from a computer (CS), Stan Input modes From-panel scan, Standard printing from a computer (CS), Stan Input modes From-panel scan, Standard printing from a computer (CS), Stan Input modes From-panel scan, Standard printing from a computer (CS), Stan Input modes From-panel scan, Standard printing from a computer (CS), Stan Input modes From-panel scan, Standard (CS), Standard		16 ppm; Black (ISO) : Up to 8.5 ppm; Color (ISO) : Up to 5.5 ppm
Print resolution Black (best) Up to 1200X 1200 rendered day (when Printing from a computer of the West) Up to 4800 x 1200 optimized dip control (when printing from a computer of ma computer of management 2.1 (1 each black, thr-color) Standard print languages Printer management No Scan speed Normal (AML to to 2.5 (pm (2000p), Black), up to 2.5 pm (200pp), color) France proper blanks (100 pm (2000p), Black), up to 2.5 pm (200pp), color) Scan speed Normal (AML to to 2.5 (pm (2000p), Black), up to 2.5 pm (200pp), color) France proper blanks (100 pm (2000p), Black), up to 2.5 pm (200pp), color) France proper blanks (100 pm (2000p), 200 pm (2000p), color) France proper blanks (100 pm (2000p), 200 pm (2000p), color) France proper blanks (100 pm (2000p), 200 pm (2000p), color) France proper blanks (100 pm (2000p), 200 pm (2000p), color) France proper blanks (100 pm (2000p), 200 pm (2000p), color) France proper blanks (100 p		
color (when printing from a computer on selected HP photo papers and 1200 input dpi) Pint catridges number 2 (1 ach ablack, tack-toolar) Standard print languages HP PCL 3 Git; HP PCLm (JP Apps/UPD); URF (ArPrint) Pinter management No San San San San speed Normal (AAL Up to 2.5 jpm (200pp), b8w); up to 2.5 jpm (200pp), c0olar) Scanner speelfications Copier specifications Copier specifications Copier specifications Copier specifications Copier specifications Fax Yes, mobile fax (seed only) Option to add files romy our phone file/photos, Camera scan or Printer scanner, Option to easily add cover page and save the cover page template, Access to Fax history to see all send faxes and drafts, Ability to edit and resent fax from History, Easily printing capability Noble printing capability Apple AirPrint** Chrome OS; HP Smart app, Mopris-certified Wineless capabilities Vis. Stulti-in-WH-18 GO21 11 a/b/g/n Network capabilities Vis. Stulti-in-WH-18 GO21 11 a/b/g/n Normal Courter in page trays Network courter in page trays Network courter in page trays Network courter	Print technology	HP Thermal Inkjet
Sandard print languages He PCL 3 GUI; HP PCLm (HP Apps/UPD); URF (Air Print) Printer management No Scan speed Normal (AAP Up to 2.5 ipm (200pp); b8w); up to 2.5 ipm (200pp); color) Scanner speel(cations Scanner type (Flathed, AU); Scan technology; Contact timage Sensor (ICS); Scan input modes Front-panel scan; Scan size maximum (WbD; 2.15.5 x 355); a mm Scan size maximum (Ratbed), 2.16 x 297 mm, Optical scan resolution Up to 1200 dp; Scanner speel(cations Scanner type (Flathed, AU); Scan technology; Contact timage Sensor (ICS); Scan input modes Front-panel scan; Scan size maximum (WbD; 2.15.5 x 355); a mm Scan size maximum (Ratbed), 2.16 x 297 mm, Optical scan resolution Up to 1200 dp; Scan file format JPEG, TIFF, PGB, BMP, PMC Copy speed Black (ISO); Up to 6 cpm; Color (SD); Up to 3 cpm Copier specifications Copier sentings. Auto-enlarge; Maximum number of copies; Up to 9 copies; Copy resolution Up to 300 x 300 dp1 Fax speed 14.4 kBps Fax speed 14.4 kBps Fax speed 14.4 kBps Fax speed 15.4 kBps Fax speed 15.4 kBps Fax speed 16.4 kBps Fax speed 16.4 kBps Fax speed 16.4 kBps Fax speed 17.4 kBps Gornectivity 1 Wireless 802.11 a/bs/gm, 1 Hi-Speed USB 2.0 Connectivity 1 Wireless 802.11 a/bs/gm, 1 Hi-Speed USB 2.0 Mobile printing capability 4 kBps Fax speed 17.4 kBps Fax speed 18.4 kBps Fax speed 19.4 kBps Fax	Print resolution	Black (best): Up to 1200X 1200 rendered dpi (when Printing from a computer); Color (best): Up to 4800 x 1200 optimized dpi color (when printing from a computer on selected HP photo papers and 1200 input dpi)
Scan Scan Normal (A4): Up to 2.5 ipm (200pp), b8w); up to 2.5 ipm (200pp), color) Scanner Specifications Copier settings Auto-enlarge: Maximum number of copies: Up to 9 copies; Copy resolution: Up to 300 x 300 dpi Fax Specifications Specifications Specifications Specifications Specifications Specifications Fax Specifications Speci	Print cartridges number	2 (1 each black, tri-color)
Scan speed Scan speed Scan speed (AdA) Lib to 2.5 jpm (2000pp), bollwy, up to 2.5 jpm (2000pp), color) Scanner speedications JPEG, TEP, DE, BMP, DE, SMP, SMP, SMP, SMP, SMP, SMP, SMP, SMP	Standard print languages	HP PCL 3 GUI; HP PCLm (HP Apps/UPD); URF (AirPrint)
Scans speed Normal (A4): Up to 2.5 jpm (200ppl, b8w); up to 2.5 jpm (200ppl, color) Scanner specifications Scanner specifications Scanner specifications Scanner specifications Scanner specifications Scanner specifications JEE, They PDE Grobe Gopy Scanner specifications JEE, They PDE Grobe Gopy Scanner specifications Discovered Black (ISO): Up to 6 cpm; Color (ISO): Up to 3 cpm Copy speed Black (ISO): Up to 6 cpm; Color (ISO): Up to 3 cpm Copier specifications Copier specifications Copier specifications Copier specifications Fax Scanner specifications Fax	Printer management	No No
Scanner specifications Scanner specifications Scanner specifications Scanner specifications JPEG, TIFF, PDE, BMP, PMG Copy Copy Sepecifications Copies specifications Fax Fax Fax Fax Fax Fax Fax Fa	Scan	
Scanner specifications	Scan speed	Normal (A4): Up to 2.5 ipm (200ppi, b&w); up to 2.5 ipm (200ppi, color)
Copy speed Slack (ISOS): Up to 6 cpm; Color (ISOS): Up to 3 cpm Copier specifications Copier settings Auto-enlarge; Maximum number of copies: Up to 9 copies; Copy resolution: Up to 300 x 300 dpi Fax Speed	Scanner specifications	maximum (ADF): 215.9 x 355.6 mm; Scan size maximum (flatbed): 216 x 297 mm; Optical scan resolution: Up to 1200 dpi;
Copier speed The Action of Copier spee	Scan file format	JPEG, TIFF, PDF, BMP, PNG
Copier specifications Copier specifications Copier specifications Fax Speed 14.4 kbps 14.4 kbp	Сору	
Fax specifications Fax Yes, mobile fax (send only) Option to add files from your phone file/photos, Camera scan or Printer scanner, Option to easily add cover page and save the Cover page tenders of the Strict of Sax history to see all send faxes and drafts, Ability to edit and resent fax from History, Easily print fax confirmation Connectivity Standard connectivity Mobile printing capability Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless capability Network organization Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** (A) Apple	Copy speed	Black (ISO): Up to 6 cpm; Color (ISO): Up to 3 cpm
Fax specifications Fax Yes, mobile fax (send only) Option to add files from your phone file/photos, Camera scan or Printer scanner, Option to easily add cover page and save the Cover page tenders of the Strict of Sax history to see all send faxes and drafts, Ability to edit and resent fax from History, Easily print fax confirmation Connectivity Standard connectivity Mobile printing capability Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless capability Network organization Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** Chrome OS; HP Smart appt, Mopria-certified Wireless (A) Apple Air/nim** (A) Apple	Copier specifications	Copier settings: Auto-enlarge; Maximum number of copies: Up to 9 copies; Copy resolution: Up to 300 x 300 dpi
Fax specifications Fax Yes, mobile fax (send only) Option to add files from your phone file/photos, Camera scan or Printer scanner, Option to easily add cover page and save the cover page template, Access to Fax history to see all send faxes and drafts, Ability to edit and resent fax from History, Easily print fax confirmation Connectivity 1 Wireless 80.2.11 a/b/g/n; 1 Hi-Speed USB 2.0 Mobile printing capability Apple Air/Print ^{19*} . (Chrome OS; HP Smart app; Mopria-certified) Wireless capability Yes, Built-in Wir-H 802.11 a/b/g/n Network capabilities Yes, built-in Wir-H 802.11 a/b/g/n Network capability Standard: 64 MB DDR1; 20 MB Flash; Maximum: 64 MB DDR1; 20 MB Flash Paper handling Automatic document feeder Standard: 35 sheet output fray: Not Applicable Output capacity Duty cycle (monthly), A4): Up to 1000 pages; Recommended monthly page volume: 100 to 300 Input capacity Standard: 35 sheet output tray: Not Applicable Output capacity Standard: 35 sheet output tray: Not Applicable Output capacity Standard: 35 sheet output tray: Not Applicable Output capacity Standard: 34 sheet years of the service of the servic	Fax	
Fax specifications Fax Yes, mobile fax (send only) Option to add files from your phone file/photos, Camera scan or Printer scanner, Option to easily add cover page and save the cover page template, Access to Fax history to see all send faxes and drafts, Ability to edit and resent fax from History, Easily print fax confirmation Connectivity 1 Wireless 80.2.11 a/b/g/n; 1 Hi-Speed USB 2.0 Mobile printing capability Apple Air/Print ^{19*} . (Chrome OS; HP Smart app; Mopria-certified) Wireless capability Yes, Built-in Wir-H 802.11 a/b/g/n Network capabilities Yes, built-in Wir-H 802.11 a/b/g/n Network capability Standard: 64 MB DDR1; 20 MB Flash; Maximum: 64 MB DDR1; 20 MB Flash Paper handling Automatic document feeder Standard: 35 sheet output fray: Not Applicable Output capacity Duty cycle (monthly), A4): Up to 1000 pages; Recommended monthly page volume: 100 to 300 Input capacity Standard: 35 sheet output tray: Not Applicable Output capacity Standard: 35 sheet output tray: Not Applicable Output capacity Standard: 35 sheet output tray: Not Applicable Output capacity Standard: 34 sheet years of the service of the servic	Fax speed	14.4 kbps
Option to add files from your phone file/photos, Camera scan or Printer scanner, Option to easily add cover page and save the cover page trenglate, Access to Fax history to see all send faxes and drafts, Ability to edit and resent fax from History, Easily print fax confirmation Connectivity 1 Wireless 802.11a/b/g/n; 1 Hi-Speed USB 2.0 Apple AirPrint™: Chrome OS; HP Smart app; Mopria-certified Wireless capability Yes, built-in Wi-Fi 802.11a/b/g/n Network capabilities Obty-speet information, 43.5 sheets Obty-speet information 43.5 shee		
Connectivity Standard connectivity 1 Wireless 802.11a/blg/n; 1 Hi-Speed USB 2.0 Apple AirPrint***(Chrome OS; HP Smart app; Mopria-certified) Wireless capability Yes, built-in Wi-Fi 802.11a/blg/n Network capabilities Yes, built-in Wi-Fi 802.11a/blg/n Network capabilities Yes, built-in Wi-Fi 802.11a/blg/n Network capabilities Yes, built-in Wi-Fi 802.11a/blg/n Standard: 64 MB DDR1; 20 MB Flash; Maximum: 64 MB DDR1; 20 MB Flash Paper handling Automatic document feeder Duty cycle (monthly) Standard: 1; Maximum: 1 Palin paper, but of applicable Output capacity Output capacity Standard: 1; Maximum: 1 Palin paper, photo paper, brothure paper, envelopes and other specialty inkjet papers Media veight A4: 60 to 90 g/m²; HP envelopes: 75 to 90 g/m²; HP cards: up to 200 g/m²; HP 10 x 15 cm photo paper: up to 300 g/m² Media size Custom (metric): 89 x 127 to 215 x 279 mm; Supported (metric): A4; B5; A6; DL envelope Printer dimensions (W x D x H) 4.82 kg What's in the box [®] Windows 10, 7: 32-bit or 64-bit, macOS v10.15 Catalina, macOS v11 Big Sur, 2 Gab ID; Internet requirements Windows 10, 7: 32-bit or 64-bit, macOS v10.15 Catalina, macOS v11 Big Sur, 2 foor Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Display LCD ICON Display, 7 Buttons (includes Power, Carcel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power) in Received in Review, WiFi, Resume & Info) Display LCD ICON Display, 7 Buttons (includes Power, Carcel, Resume, Info, WiFi, Libror Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Display LCD ICON Display, 7 Buttons (includes Power, Carcel, Resume, Info, WiFi, Libror Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) LCD ICON Display, 7 Buttons (includes Power,		Option to add files from your phone file/photos, Camera scan or Printer scanner, Option to easily add cover page and save the cover page template, Access to Fax history to see all send faxes and drafts, Ability to edit and resent fax from History, Easily
Standard connectivity 1 Wireless 802.11a/b/g/n; 1 Hi-Speed USB 2.0 Mobile printing capability ⁶ Apple AirPrintin ¹⁹ ; Chrome 05; HP Smart app; Mopria-certified Wireless capability Yes, built-in Wi-Fi 802.11a/b/g/n Network capabilities Yes, built-in Wi-Fi 802.11a/b/g/n Network capabilities Yes, built-in Wi-Fi 802.11a/b/g/n Network capabilities Yes, built-in Wi-Fi 802.11a/b/g/n Nemory Standard: 64 MB DDR1; 20 MB Flash; Maximum: 64 MB DDR1; 20 MB Flash Paper handling Automatic document feeder Standard, 35 sheets Duty cycle (monthly) Duty cycle (monthl	Connectivity	
Mobile printing capability		1 Wireless 802 11a/h/a/n: 1 Hi-Speed USR 2 0
Wireless capability Ves, built-in Wi-Fi 802.11a/b/g/n Network capabilities Yes, built-in Wi-Fi 802.11a/b/g/n Memory Standard: 64 MB DDR1; 20 MB Flash; Maximum: 64 MB DDR1; 20 MB Flash Paper handling Automatic document feeder Standard; 35 sheets Duty cycle (monthly) Duty cycle (mont		
Network capabilities Ves, built-in Wi-Fi 802.11a/b/g/n Memory Standard: 64 MB DDR1; 20 MB Flash; Maximum: 64 MB DDR1; 20 MB Flash Paper handling Automatic document feeder Standard, 35 sheets Duty cycle (monthly) Duty cycle (monthly) Duty cycle (monthly) Duty cycle (monthly) 60-sheet input tray; Not Applicable Output capacity 25-sheet output tray Number of paper trays Standard: 1; Maximum: 1 Media types Media veight A4: 60 to 90 g/m²; HP envelopes: 75 to 90 g/m²; HP cards: up to 200 g/m²; HP 10 x 15 cm photo paper: up to 300 g/m² Media size Custom (metric): 89 x 127 to 215 x 279 mm; Supported (metric): A4; B5; A6; DL envelope Pinter dimensions (W x D x H) 4.82 kg What's in the box ⁸ HP Desklet 41 20e All-in-One Printer; HP 67 Setup Black Cartridge; HP 67 Setup Tri-Color Cartridge; Regulatory flyer; Setup guide; Reference guide; Power cord [For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies] One-year limited hardware warranty; 24-hour, 7 days a week support Systems Compatible operating systems Windows: 10, 7: 32-bit or 64-bit, acc 55 v10.14 Mojave, mac05 v10.15 Catalina, mac05 v11 Big Sur, Chrome 05 Windows vindows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer; Mac mac0 v10.14 Mojave, mac05 v10.15 Catalina, mac05 v10.15 Gastlina, mac05 v10.15 Catalina, mac05 v10.15 Cata		
Memory Paper handling Automatic document feeder Duty cycle (monthly) Duty cycle (monthly, Ad): Duty cycle (monthly page volume: 100 to 300 Duty cycle (monthly adversarial) Duty cycle (monthly, Ad): Duty cycle (monthly page volume: 100 to 300 Duty cycle (monthly, Ad): Duty cycle (monthly page volume: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). (China Shids): Consumption (TEC): 0.18 kWh/Week; Power supply type: Internal Departing temperature ange: 51 to 40°C. Recommended operating humidity range: 20 to 80% RH (non-condensing): Recommended operating humidity range: 20 to 80% RH (non-condensing): Recommended operating humidity range:		
Paper handling		-
Automatic document feeder Duty cycle (monthly) Duty capacity Duty capacity Duty capacity Standard. 1; Maximum: 1 Media lypes Plain paper, photo paper, brochure paper, envelopes and other specialty inkjet papers Media weight Ad: 60 to 90 g/m²; HP envelopes: 75 to 90 g/m², HP cards: up to 200 g/m²; HP 10 x 15 cm photo paper: up to 300 g/m² Media size Custom (metric): 89 x 127 to 215 x 279 mm; Supported (metric): A4; B5; A6; DL envelope Printer dimensions (W x D x H) Printer weight 4.82 kg What's in the box ⁸ HP DeskJet 4120e All-in-One Printer; HP 67 Setup Black Cartridge; HP 67 Setup Tri-Color Cartridge; Regulatory flyer; Setup guide; Reference guide; Power cord [For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies] Warranty One-year limited hardware warranty; 24-hour, 7 days a week support Systems Compatible operating systems Windows Windows 10, 7: 32-bit or 64-bit, mac0S v10.14 Mojave, mac0S v10.15 Catalina, mac0S v11 Big Sur; C forme 05 Windows Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer:, Mac mac0' v10.14 Mojave, mac0S v10.15 Catalina, mac0S v10.15 Catalina, mac0S v10.15 Color Display 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Display LCD ICON Display 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power ink level, WiFi, Resume & Info) Operating environment Operating temperature range 15 to 30°C Operating environment Operating temperature range 15 to 30°C Operating temperature range 15 to 30°C Operating temperature range 15 to 80% RH (non-condensing); Recommended operating humidity range: 20 to 80% RH (non-condensing) Sustainable impact specifications Acou		Stalidard, 04 Mb DDK1, 20 Mb Flash, Maximum, 04 Mb DDK1, 20 Mb Flash
Duty cycle (monthly) Duty capacity 60-sheet input tray; Not Applicable Output capacity 25-sheet output tray Not Applicable Dutput capacity Standard: Naximum: 1 Media types Plain paper; photo paper, brochure paper, envelopes and other specialty inkjet papers Media weight Ad: 60 to 90 g/m²; HP envelopes: 75 to 90 g/m²; HP cards: up to 200 g/m²; HP 10 x 15 cm photo paper; up to 300 g/m² Media size Custom (metric): 89 x 127 to 215 x 279 mm; Supported (metric): Ad; B5; A6; DL envelope Printer dimensions (W x D x H) 428 x 332 x 200 mm Printer weight 482 kg What's in the box ⁸ HP DeskJet 4120e All-in-One Printer; HP 67 Setup Black Cartridge; HP 67 Setup Tri-Color Cartridge; Regulatory flyer; Setup guide; Reference guide; Power cord [For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies] One-year limited hardware warranty; 24-hour, 7 days a week support Systems Compatible operating systems Windows 10, 7: 32-bit or 64-bit, macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, Chrome OS Windows (Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer.; Mac macOs v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, 2 GB HD (Internet required LCD ICON Display. 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Power ² Requirements: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 19%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 19%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240		Characterist 25 shorts
Input capacity 60-sheet input tray; Not Applicable Output capacity 25-sheet output tray Number of paper trays Standard: 1; Maximum: 1 Media types Plain paper, photo paper, broto paper, brochure paper, envelopes and other specialty inkjet papers Media weight A4: 60 to 90 g/m²; HP envelopes: 75 to 90 g/m²; HP cards: up to 200 g/m²; HP 10 x 15 cm photo paper: up to 300 g/m² Media size Custom (metric): 89 x 127 to 215 x 279 mm; Supported (metric): A4; B5; A6; DL envelope Printer dimensions (W x D x H) ³ 4.82 kg HP Desk.let 4120e All-in-One Printer; HP 67 Setup Black Cartridge; HP 67 Setup Tri-Color Cartridge; Regulatory flyer; Setup guide; Reference guide; Power cord [For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies] Warranty One-year limited hardware warranty; 24-hour, 7 days a week support Systems Compatible operating systems Windows 10, 7: 32-bit or 64-bit, mac05 v10.14 Mojave, mac05 v10.15 Catalina, mac0S v11 Big Sur, Chrome 0S Windows Windows 10, 7: 32-bit or 64-bit, a GB available hard disk space, Internet connection, Internet Explorer.; Mac mac05 v10.14 Mojave, mac0S v10.15 Catalina, mac0S v10.1		
Output capacity 25-sheet output tray Number of paper trays Standard: 1; Maximum: 1 Media types Plain paper, photo paper, brochure paper, envelopes and other specialty inkjet papers Media weight A4: 60 to 90 g/m²; HP envelopes: 75 to 90 g/m²; HP cards: up to 200 g/m²; HP 10 x 15 cm photo paper: up to 300 g/m² Media size Custom (metric): 89 x 127 to 215 x 279 mm; Supported (metric): A4; B5; A6; DL envelope Printer dimensions (W x D x H) ¹ 428 x 332 x 200 mm Printer weight 4.82 kg HP Desklet 4120e All-in-One Printer; HP 67 Setup Black Cartridge; HP 67 Setup Tri-Color Cartridge; Regulatory flyer; Setup glide; Reference guide; Power cord [For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies] Warranty One-year limited hardware warranty; 24-hour, 7 days a week support Systems Compatible operating systems Windows: Windows 10, 7: 32-bit or 64-bit, mac0S v10.14 Mojave, mac0S v10.15 Catalina, mac0S v11 Big Sur, Chrome 0S Winimum system requirements Windows: Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer.; Mac mac0S v10.14 Mojave, mac0S v10.15 Catalina, mac0S v11 Big Sur, Chrome 0S UCD ICON Display, 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Display LCD ICON Display Requirements: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 20 to 0 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 20 to 80% RH (non-condensing) Operating environment Operating emperature range: 5 to 40°C; Recommended operating temperature range: 15 to 30°C Operating humidity range: 15 to 80% RH (non-condensing); Recommended operating humidity range: 20 to 80% RH (non-condensing); Recommended operating humidity range: 20 to 80% RH (non-condensing); Recommended operating humidi		
Number of paper trays Standard: 1; Maximum: 1 Media types Plain paper, photo paper, brochure paper, envelopes and other specialty inkjet papers Media weight A4: 60 to 90 g/m²; HP envelopes: 75 to 90 g/m²; HP cards: up to 200 g/m²; HP 10 x 15 cm photo paper: up to 300 g/m² Media size Custom (metric): 89 x 127 to 215 x 279 mm; Supported (metric): A4; B5; A6; DL envelope Printer dimensions (W x D x H) ¹ 4.82 kg HP DeskJet 4120e All-in-One Printer; HP 67 Setup Black Cartridge; HP 67 Setup Tri-Color Cartridge; Regulatory flyer; Setup guide; Reference guide; Power cord (For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies) Warranty One-year limited hardware warranty; 24-hou; 7 days a week support Systems Compatible operating systems Windows 10, 7: 32-bit or 64-bit, macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, Chrome OS Windows vindows 10, 7: 32-bit or 64-bit, a 26 available hard disk space, internet connection, Internet Explorer; Mac macOs v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, 2 GB HD; Internet required Control panel LCD ICON Display, 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Display Requirements: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/		
Media types Plain paper, photo paper, brochure paper, envelopes and other specialty inkjet papers Media weight A4: 60 to 90 g/m²; HP envelopes: 75 to 90 g/m²; HP cards: up to 200 g/m²; HP 10 x 15 cm photo paper: up to 300 g/m² Media size Custom (metric): 89 x 127 to 215 x 279 mm; Supported (metric): A4; B5; A6; DL envelope Printer dimensions (W x D x H) ¹ 428 x 332 x 200 mm Printer weight 4.82 kg HP Desklet 4120e All-in-One Printer; HP 67 Setup Black Cartridge; HP 67 Setup Tri-Color Cartridge; Regulatory flyer; Setup guide; Reference guide; Power cord [For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies] Warranty One-year limited hardware warranty; 24-hou; 7 days a week support Systems Compatible operating systems Windows 10, 7: 32-bit or 64-bit, mac0S v10.14 Mojave, mac0S v10.15 Catalina, mac0S v11 Big Sur, Chrome 0S Windows Windows 10, 7: 32-bit or 64-bit, and Survailable hard disk space, Internet connection, Internet Explorer; Mac mac0S v10.14 Mojave, mac0S v10.15 Catalina, mac0S v11 Big Sur, Chrome 0S Windows Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer; Mac mac0S v10.14 Mojave, mac0S v10.15 Catalina, mac0S v10.15 Mojave, mac0S v10.15 Catalina, mac0S v10.15 Catalina, mac0S v10.15 Catalina, mac0S v10.15 Mojave, mac0S v10.15 Catalina, mac0		
Media weight A4: 60 to 90 g/m²; HP envelopes: 75 to 90 g/m²; HP cards: up to 200 g/m²; HP 10 x 15 cm photo paper: up to 300 g/m² Media size Custom (metric): 89 x 127 to 215 x 279 mm; Supported (metric): A4; B5; A6; DL envelope Printer dimensions (W x D x H) ¹ 4.82 x 332 x 200 mm Printer weight 4.82 kg HP Desk.let 4120e All-in-One Printer; HP 67 Setup Black Cartridge; HP 67 Setup Tri-Color Cartridge; Regulatory flyer; Setup guide; Reference guide; Power cord [For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies] Warranty One-year limited hardware warranty; 24-hour, 7 days a week support Systems Compatible operating systems Windows: Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer.; Mac mac05 v10.14 Mojave, mac05 v10.15 Catalina, mac05 v11 Big Sur, Chrome 05 Windows: Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer.; Mac mac05 v10.14 Mojave, mac05 v10.15 Catalina, mac05 v11 Big Sur, 2 GB HD; Internet required Control panel LCD ICON Display, 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink Level, WiFi, Resume & Info) Power ² Requirements: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input volta		
Media size Custom (metric): 89 x 127 to 215 x 279 mm; Supported (metric): A4; B5; A6; DL envelope Printer dimensions (W x D x H) ¹ 428 x 332 x 200 mm Printer weight 4.82 kg What's in the box ⁸ HP DeskJet 4120e All-in-One Printer; HP 67 Setup Black Cartridge; HP 67 Setup Tri-Color Cartridge; Regulatory flyer; Setup guide; Reference guide; Power cord [For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies] Warranty One-year limited hardware warranty; 24-hour, 7 days a week support Systems Compatible operating systems Windows 10, 7: 32-bit or 64-bit, macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, Chrome OS Winimum system requirements Windows: Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer; Mac macOs v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, 2 GB HD; Internet required LCD ICON Display, 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink Level, WiFi, Resume & Info) Display LCD ICON Display, 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink Level, WiFi, Resume & Info) Power ² Requirements: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage	Media types	
Printer dimensions (W x D x H) ¹ 4.82 kg What's in the box ⁸ HP DeskJet 4120e All-in-One Printer; HP 67 Setup Black Cartridge; HP 67 Setup Tri-Color Cartridge; Regulatory flyer; Setup glide; Reference guide; Power cord [For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies] Warranty One-year limited hardware warranty; 24-hour, 7 days a week support Systems Compatible operating systems Windows 10, 7: 32-bit or 64-bit, macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, Chrome OS Winimum system requirements Windows: Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer; Mac macOs v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, Chrome OS V10.14 Mojave, macOS v10.15 Catalina, macOS v10.15 Catalina, macOS v10.16 Kg Space, Internet connection, Internet Explorer; Mac macOs v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, 2 GB HD; Internet required LCD ICON Display, 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Display LCD ICON Display, 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Power ² Requirements: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200		
Printer weight 4.82 kg What's in the box ⁸ What's in the box's in the box's in the box's power by the box's in the box's power box's in the box's in the box's in the box's power box's in the box's in the box's in the box's in the box's power box's in the box's in t		
What's in the box ⁸ HP DeskJet 4120e All-in-One Printer; HP 67 Setup Black Cartridge; HP 67 Setup Tri-Color Cartridge; Regulatory flyer; Setup guide; Reference guide; Power cord [For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies] One-year limited hardware warranty; 24-hour, 7 days a week support Systems Compatible operating systems Windows 10, 7: 32-bit or 64-bit, macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, Chrome OS Windows: Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, internet connection, Internet Explorer.; Mac macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, 2 GB HD; Internet required Control panel LCD ICON Display. 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Display LCD ICON Display. 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Power ² Requirements: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC	Printer dimensions (W x D x H) ¹	428 x 332 x 200 mm
whats in the obx guide; Reference guide; Power cord [For ink volume and page yield information, visit http://hp.com/go/fearnaboutsupplies] Warranty One-year limited hardware warranty; 24-hour, 7 days a week support Systems Compatible operating systems Windows: Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer.; Mac macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, Chrome OS Windows: Windows: 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer.; Mac macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, 2 GB HD; Internet required Control panel LCD ICON Display 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Display LCD ICON Display 1.00 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input v	Printer weight	- 3
Systems Compatible operating systems Windows 10, 7: 32-bit or 64-bit, mac0S v10.14 Mojave, mac0S v10.15 Catalina, mac0S v11 Big Sur, Chrome 05 Windows: Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer; Mac mac0S v10.14 Mojave, mac0S v10.15 Catalina, mac0S v10.18 (ps. vinc. 10.14 Mojave, mac0S v10.15 Catalina, mac0S v10.18 (ps. vinc. 10.14 Mojave, mac0S v10.15 Catalina, mac0S v10.18 (ps. vinc. 10.14 Mojave, mac0S v10.15 Catalina, mac0S v10.18 (ps. vinc. 10.15 Catalina, mac0S v11 Big Sur, Chrome 05 UCD ICON Display. LCD ICON Display. 1 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) LCD ICON Display. 1 LCD ICON Display		guide; Reference guide; Power cord [For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies]
Minimum system requirements Windows 10, 7: 32-bit or 64-bit, macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, Chrome OS Windows: Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer.; Mac macOS v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur, 2 GB HD; Internet required Control panel LCD ICON Display. 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Display LCD ICON Display Requirements: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). (China & India); Consumption: 2.5 Walts (Ready); 1.1 Walts (Sleep); 0.15 Walts (Off); 0.15 Walts (Auto-off); Typical Electricity Consumption (TEC): 0.18 kWh/Week; Power supply type: Internal Operating environment Operating temperature range: 5 to 40°C; Recommended operating temperature range: 15 to 30°C Operating humidity range: 15 to 80% RH (non-condensing); Recommended operating humidity range: 20 to 80% RH (non-condensing) None Acoustics Acoustic power emissions (active printing): 6.2 B(A); Acoustic power emissions (active copy): 6.2 B(A); Acoustic pressure emissions: 56 dB(A)		One-year limited hardware warranty; 24-hour, 7 days a week support
Minimum system requirements Windows: Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer.; Mac macOs v10.14 Mojave, macOs v10.15 Catalina, macOs v11 Big Sur; 2 GB HD; Internet required LCD ICON Display. 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink level, WiFi, Resume & Info) Display LCD ICON Display Requirements: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). (China & India); Consumption: 2.5 Watts (Ready); 1.1 Watts (Sleep); 0.15 Watts (Off); 0.15 Watts (Auto-off); Typical Electricity Consumption (TEC): 0.18 kWh/Week; Power supply type: Internal Operating environment Operating temperature range: 5 to 40°C; Recommended operating temperature range: 15 to 30°C Operating humidity range: 15 to 80% RH (non-condensing); Recommended operating humidity range: 20 to 80% RH (non-condensing) None Acoustics Acoustic power emissions (active printing): 6.2 B(A); Acoustic power emissions (active copy): 6.2 B(A); Acoustic pressure emissions: 56 dB(A) Escentia Power of the Internation of the Color of the Internation of the Color of the Internation of In		
V10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur; 2 GB HD; Internet required Control panel LCD ICON Display, 7 Buttons (includes Power, Cancel, Resume, Info, WiFi, Color Copy and Black Copy) and with 5 LED indicator lights (Power, Ink Level, WiFi, Resume & Info) Display LCD ICON Display Requirements: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 H		Windows: Windows 10, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Internet Explorer.; Mac mac0s
LCD ICON Display Requirements: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240		v10.14 Mojave, macOS v10.15 Catalina, macOS v11 Big Sur; 2 GB HD; Internet required
Requirements: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz. Input voltage: 200 to 240 VAC (+/- 10%), 50/60 Hz		lights (Power, Ink level, WiFi, Resume & Info)
Power ² Hz (+/- 3Hz) (China & India); Consumption: 2.5 Watts (Ready); 1.1 Watts (Sleep); 0.15 Watts (Off); 0.15 Watts (Auto-off); Typical Electricity Consumption (TEC): 0.18 kWh/Week; Power supply type: Internal Operating temperature range: 5 to 40°C; Recommended operating temperature range: 15 to 30°C Operating humidity range: 15 to 80% RH (non-condensing); Recommended operating humidity range: 20 to 80% RH (non-condensing) Sustainable impact specifications None Acoustics Acoustic power emissions (active printing): 6.2 B(A); Acoustic power emissions (active copy): 6.2 B(A); Acoustic pressure emissions: 56 dB(A) Sefetu apprendix and requirements IEC 60950-1:2005 +A1:2009 +A2:2013, EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013, IEC 62368-1:2014,		
Operating humidity range: 15 to 80% RH (non-condensing); Recommended operating humidity range: 20 to 80% RH (non-condensing) Sustainable impact specifications None Acoustics Acoustic power emissions (active printing): 6.2 B(A); Acoustic power emissions (active copy): 6.2 B(A); Acoustic power	Power ²	Hz (+/- 3Hz) (China & India); Consumption: 2.5 Watts (Ready); 1.1 Watts (Sleep); 0.15 Watts (Off); 0.15 Watts (Auto-off); Typical Electricity Consumption (TEC): 0.18 kWh/Week; Power supply type: Internal
Acoustics Acoustic power emissions (active printing): 6.2 B(A); Acoustic power emissions (active copy): 6.2 B(A); Acoustic pressure emissions: 56 dB(A) Sefety approaches and requirements. IEC 60950-1:2005 +A1:2009 +A2:2013, EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013, IEC 62368-1:2014,	Operating environment	Operating humidity range: 15 to 80% RH (non-condensing); Recommended operating humidity range: 20 to 80% RH (non-
emissions: 56 dB(A) Sefety approaches and requirements. IEC 60950-1:2005 +A1:2009 +A2:2013, EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013, IEC 62368-1:2014,	Sustainable impact specifications	None
	Acoustics	
	Safety approvals and requirements	

Ordering information

Number	Description
26Q94A	HP DeskJet 4120e All-in-One Printer (White) - AU/NZ
26Q95A	HP DeskJet 4121e All-in-One Printer (Cement) - AU/NZ
26Q96A	HP DeskJet 4122e All-in-One Printer (Light Sage) - AU/NZ
26Q97A	HP DeskJet 4123e All-in-One Printer (Indigo) - AU/NZ

Supplies and Media

Number	Description
3YM55AA	HP 67 Tri-color Original Ink Cartridge
3YM56AA	HP 67 Black Original Ink Cartridge
3YM57AA	HP 67XL High Yield Black Original Ink Cartridge
3YM58AA	HP 67XL High Yield Tri-color Original Ink Cartridge
3YM59AA	HP 67XXL Extra High Yield Black Original Ink Cartridge
9RR49A	HP Advanced Glossy FCS Photo Paper-100 sht/10 x 15 $$ cm
9RR50A	HP Advanced Glossy FCS Photo Paper-50 sht/10 x 15 cm $$
9RR51A	HP Advanced Glossy FCS Photo Paper-20 sht/A4/210 x 297 mm
C6065A	HP Iron-on Transfers-12 sht/A4/210 x 297 mm

Contact HP via phone: Asia: 65 6253 8500

HP Care Packs

Number	Description
UG062E	HP 3 year Care Pack Next Business Day Exch Multi Fcn Printer - E SVC
UG457E	HP 3 year Care Pack Onsite Exch Multi Fcn Prtr - E SVC
UG235E	HP 3 year Care Pack Return Multi Fcn Printer - E SVC
UG337E	HP 3 year Care Pack Pickup Rtn Multi Fcn Printer -E SVC
U6N05E	HP Installation w/Network Consumer Printer SVC

Protect your investment with HP Care Pack. Let HP certified engineers resolve your technical issues. For more details on HP Care Pack, go to hp.com/go/cpc

HP Inc. offices

Australia 13 10 47 hp.com.au New Zealand (09) 0800 449 553 hp.co.nz















Technical specifications disclaimers

Dimensions vary as per configuration

Power requirements are based on the destroyl/region where the printer is said. On not convert operating voltages. This will damage the printer and void the product warranty.

A requirements are based on the destroyl/region where the printer is said. On not convert operating voltages. This will damage the printer and void the product warranty.

A requirements are based on the destroyler operation of the printer operation oper

