

Excel in the digital world



The ECOSYS PA4000cx is an A4 versatile colour printing solution, built with Kyocera's renowned durable components that help to reduce your organisation's environmental footprint while providing outstanding reliability and productivity. The device also allows for different media sizes and weights, up to 220g/m2.



ECOSYS PA4000cx



Low running costs

Up to 40 pages per minute

Standard double-sided print

Specifications

GENERAL

KYOCERA ECOSYS Laser Colour Printer

Operation panel: 5Line display with back light and numeric keypad

Type: Desktop

Engine speed Simplex: Up to 40 pages A4 per minute.

Engine speed Duplex: Up to 33 pages A4 per minute.

Resolution: 1200 x 1200 dpi (print),

600 x 600 dpi (scan/copy)

Recommended Print Volume: 1,900 images per month

Maximum Life: 600,000 images or 5 years

Warm-up time: Approx. 21 seconds or less

Time to first print: Approx. 5.4 seconds or less

CPU: ARM Cortex-A9 Dual core 1.2GHz

Memory: Standard 1 GB, Max. 3 GB (optional)

Standard interfaces: USB 2.0 (Hi-Speed), 2 x USB Host

Interface, Gigabit Ethernet (10BASE-T/100BASE-TX

/1000BASE-T), optional Wireless LAN (IEEE 802.11b/g/n),

1 x eKUIO slot for optional devices other than FAX, Slot for

optional SD Card

Integrated accounting: 100 department codes

Dimensions (W x D x H): Without packaging:

394 x 531.5 x 455 mm (without protrusions);

394 x 533 x 455 mm (including protrusions);

With packaging: 702 x 567 x 561 mm

Weight: Without packaging:

Approx. 34 kg (with bundled toner)

Approx. 33 kg (without bundled toner)

With packaging: 41 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption:

Printing: 533.3W

Ready mode: 11.8 W

Sleep-mode: 0.4 W (default)

Noise (sound pressure level: ISO 7779/ISO 9296):

Operating: 53 dB (LpAm)

Stand-by: 30 dB (LpAm)

Safety standards: TÜV/GS, CE

This unit is manufactured according to ISO 9001 quality

standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of

max. 0.11 mm. Please use paper recommended by KYOCERA

under normal environmental conditions.

Input capacity: Multi-purpose tray: 100 sheets (80 g/

m² equivalent), 110 sheets (64 g/m² equivalent.)

60–220 g/m², A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom

(70 x 140 to 216 x 356 mm), Banner paper

up to 1220 mm. Standard universal paper cassette:

550 sheet with 75 g/m², 600 sheet with 64 g/m²

60–220 g/m², A4, A5, A6, B5, B6, Letter, Legal,

Folio, Custom (105 x 140 to 216 x 356 mm).

Max. input capacity with options: 2,300 sheets

with 75 g/m², 2,510 sheets with 64 g/m²

Duplex: Standard duplex unit 60–163 g/m². A4, A5, A6,

B5, Letter, Legal, Custom (140 x 210 mm - 216 x 356 mm).

Output capacity: 500 sheets (Equivalent to 80 g/m²) face

down with paper full sensor

PRINT FUNCTIONS

Controller language: PRESCRIBE

Emulations: PCL6 (5c/XL), KPDL3 (PostScript 3 compatible),

PDF, XPS, Open XPS, TIFF, JPEG, URF, PWG Raster, PCLm

Operating systems: All current Windows operating systems,

MAC OS X Version 10.9 or higher, Chrome OS, Linux,

as well as other operating systems on request

Fonts/barcodes: 93 outline fonts (PCL6, KPDL3), 4 fonts

(Calibri), 4 fonts (Cambria), 1 Bitmap font, 45 types of

one-dimensional barcodes, 1 type of two-dimensional

barcode (PDF417)

Print features: PDF Direct Print, Internet printing IPP

1.0, E-mail printing, WSD print, secure printing IPP over

TLS, Local and network authentication, Network data

encryption IPsec, HTTPS, LDAP over TLS, SNMPv3,

SMTP over TLS, POP over TLS, Encrypted PDF Direct

Print, TLS 1.3, Secure Boot, Run-time Integrity Check,

Microsoft Universal Print, Printing for Chrome OS

Mobile printing support: KYOCERA Mobile Print app for

iOS and Android, AirPrint, Mopria, Microsoft Universal Print,

Wi-Fi Direct (Opt)

CONSUMABLES

Average continuous toner yield in accordance with ISO 19798

TK-5384K: Black 13,000 pages A4

TK-5384Y, TK-5384M, TK-5384C: Yellow, Magenta and Cyan

10,000 pages A4

Starter toner black 6,000 pages and Yellow, Magenta and

Cyan 5,000 pages A4

OPTIONS

PF-5150 Paper feeder: Max. 550 sheet with 75 g/m², 600 sheet

with 64 g/m², 60 - 220 g/m², A5R - Legal, 92.1 x 165.1 (Com6),

114x162 (Youkei2), Max 3 Units

1244/10 Cabinet: for 2-draw configuration

Memory upgrade: 1GB/2GB

Storage Devices for easy document management:

HD-17 SSD hard disk: 64GB

HD-18 SSD hard disk: 256GB

HD-19 SSD hard disk: 512GB

SECURITY OPTIONS

UG-33 AC: ThinPrint support

UG-35: TPM (Trusted Platform Module)

USB IC Card Reader + Card Authentication Kit (B):

Support for various authentication keys available.

CRH 12: Card Reader Holder 12

Optional interface:

IB-37: Wireless LAN (802.11a/b/g/n/ac) with Wi-Fi Direct

IB-50: Gigabit Ethernet 10BASE-T/100BASE-TX/

1000BASE-T

IB-51: Wireless LAN Interface (802.11b/g/n)

WARRANTY

2 year on-site as standard.

WHAT'S IN THE BOX:

Main unit, initial toner, waste toner box, Quick guide,

Safety Guide, Operation panel sheet, power supply cord.

ECOSYS stands for ECOlogy, ECOmy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.



JUN2023ECOSYSPA4000cx/VER1.0

KYOCERA Document Solutions Australia

Ph: 13 59 62

www.kyoceradocumentsolutions.com.au

KYOCERA Document Solutions New Zealand

Ph: 0800 459 623

www.kyoceradocumentsolutions.co.nz



* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free.

Specifications are subject to change without notice. Information is correct at time of going to press.

All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

** Depending on the country