

Datasheet FUJITSU Image Scanner fi-7030

Evolved entry model suitable for quick scanning



The fi-7030 scans A4 portraits at 27 ppm/54 ipm (200/300 dpi), loads up to 50 sheets at a time, and ensures efficiency with quick startup times and a small footprint.

Boosted usability with a user-friendly and compact design

The scanner's compact design, even smaller than A4 sheets, makes it suitable for use anywhere: on desks, at reception counters, and wherever you desire. No more waiting with quick startup times of half a second and recovery times of a mere second when resuming from sleep mode. Scan up to 9 jobs with a single push of a button and reduce repetitive and time-consuming tasks before and after scanning, using the scanner's automatic image processing functions: Automatic Size Detection, Automatic Color Detection, and Blank Page Detection.

Assistance for safe and reliable scanning

The fi-7030 scans documents of various thicknesses, including plastic cards and embossed cards. Scan documents exceeding 5 meters in length as well as A3 documents with optional carrier sheets. And bid farewell to missing edges with the scanner's Skew Reducer mechanism. Potential information loss, resulting from multiple sheets being fed through the scanner at once, is also no longer an issue with Brake roller separation and Ultrasonic Multi-feed detection.

Easy managing of dispersed operations

Share user-specific operational environments and customized scan jobs, as well as monitor scanning errors and life of consumable parts with Scanner Central Admin. Monitoring and managing of dispersed tasks throughout vast networks are now easier than ever before.

Advanced software for enhanced efficiency

The PaperStream IP scanner driver, supporting both TWAIN and ISIS, enables you to bypass the inconvenience of making fine adjustments to OCR settings. The software automatically converts scanned images into exceptionally clean images, supporting OCR accuracy even when scanning documents with background patterns or wrinkled and soiled documents. Seamlessly linked to PaperStream IP, PaperStream Capture effectively and efficiently feeds information into your organization workflow with its various batch scanning capture features. Automatically utilizing data extracted from barcodes and patch codes, the software determines your preferred saving destinations and eliminates time allocated to routine tasks.

Technical Information

Scanner Type	ADF (Automatic Document Feeder), Duplex
Scanning Speed*1 (A4 Portrait) (Color*2/Grayscale*2/Monochrome*3)	Simplex: 27 ppm (200/300 dpi) Duplex: 54 ipm (200/300 dpi)
Image Sensor Type	Color CIS x 2 (front x 1, back x 1)
Light Source	3 Color LED x 2 (front x 1, back x 1)
Optical Resolution	600 dpi
Output Resolution** (Color / Grayscale / Monochrome)	50 to 600 dpi (adjustable by 1 dpi increments), 1,200 dpi (driver) ^{*5}
Output Format	Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit
Background Colors	White
Document Size	
Maximum* ⁶	216 x 355.6 mm (8.5 x 14 in.)
Minimum	50.8 x 50.8 mm (2 x 2 in.)
Long Page Scanning*7 (Maximum)	5,588 mm (220 in.)
Paper Weight (Thickness)	
Paper	40 to 209 g/m² (11 to 56 lb)*8
Plastic Card	0.76 mm (0.0299 in.) or less*9
ADF Capacity ^{*10*11}	50 sheets (A4 80 g/m ² or Letter 20 lb)
Typical Daily Duty Cycle ^{*12}	2,500 sheets
Multifeed Detection	Overlap detection (Ultrasonic sensor), Length detection
Interface	USB 2.0 / USB 1.1
Power Requirements	AC 100 to 240 V ±10 %
Power Consumption	
Operating Mode	17 W or less
Sleep Mode	1.1 W or less
Auto Standby (Off) Mode	0.15 W or less
Operating Environment	
Temperature	5 to 35 °C (41 to 95 °F)
Relative Humidity	20 to 80% (non-condensing)

Environmental Compliance	ENERGY STAR [®] , RoHS
Dimensions ^{*13} (Width x Depth x Height)	290 x 146 x 130 mm (11.4 x 5.7 x 5.1 in.)
Weight	2.9 kg (6.4 lb)
Supported Operating System	Windows® 10 (32-bit/64-bit), Windows® 8.1 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Server® 2016 (64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2012 (64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2008 (32-bit/64-bit), Linux Ubuntu* ¹⁶
Included Software / Drivers	PaperStream IP Driver (TWAIN/TWAIN x64/ISIS), WIA Driver* ¹⁵ , PaperStream Capture, ScanSnap Manager for fi Series ^{*16} , Software Operation Panel, Error Recovery Guide, ABBYY FineReader for ScanSnap ^{M*16} , Scanner Central Admin
Image Processing Functions	Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, Dither, De-Screen, Emphasis, Dropout color (None/Red/Green/Blue/White/Saturation/Custom), sRGB output, Split image, De-Skew, Edge filler, Vertical streaks reduction, Cropping, Dither, Static threshold, Moire removal
Included Items	ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM

Options

PaperStream Capture Pro Scan Station (WG)	PA43404-A665 PaperStream Capture Pro optional license
Carrier Sheets	PA03360-0013 Each package contains 5 carrier sheets
2D Barcode for PaperStream	PA43404-A433 Reads PDF417, QR code, Data Matrix, Aztec Code

Consumables Roller Set PA03706-0001 Brake Roller Pick Roller Every 200,000 sheets or one year

*1 Actual scanning speeds are affected by data transmission and software processing times. *2 Indicated speeds are from using JPEG compression. *3 Indicated speeds are from using TIFF CCITT Group 4 compression. *4 Selectable maximum density may vary depending on the length of the scanned document. *5 Some limitations may apply to the size of documents that can be scanned, depending on system environment, when scanning at high resolution (over 600 dpi). *6 Scans folded documents of up to 297 x 432 mm (11.7 x 17 in.) with carrier sheet scanning, *7 Capable of scanning documents longer than A4 (210 x 297 mm / 8.3 x 11.7 in.) sizes. When using PaperStream IP (TWAIN/ISIS) to scan at 200 dpi, the maximum scanning length is 5,588 mm (220 in.). *8 Thicknesses of up to 127 to 209 g/m² (34 to 56 lb) can be scanned for A8 (52 x 74 mm / 2.1 x 2.9 in.) sizes. "9 Multiple cards cannot be set continuously (Note: capable of scanning embossed cards). *10 Maximum capacity depends on paper weight and may vary. *11 Capable of scanning and occuments while scannery. *12 When operating 8 hours a day. *13 Excludes the ADF paper chute and stacker. *14 Availability of support may vary depending on region. Some functions may not be available with the WIA Driver. *16 Software can be downloaded from the website designated in the Setup DVD-ROM.

Trademarks

ABBYY^M FineReader^M Engine © ABBYY. OCR by ABBYY. ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions. ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies. Safety Precautions

Be sure to carefully read all safety precautions prior to using this product and use this device as instructed. Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product. Be sure to limit the use of this product to listed power ratings. ENERGY STAR®

PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

Specifications are subject to change without notice. Visit the fi Series website for more information. http://imagescanner.fujitsu.com/

Contact