

Powered by

PRECISIONCORE

SPECIFICATION SHEET

WorkForce[®] Pro WF-M5799 Replaceable Ink Pack System

Wireless | Print | Copy | Scan | Email | Fax Ethernet | PCL¹/PS



Print up to 33,000 more pages, before you replace the ink²

Powered by PrecisionCore[®] — the next-generation of inkjet printing technology; plus Epson's innovative Replaceable Ink Pack System

More prints, less cost – Epson ink lasts up to 33,000 pages longer² than its competition to help reduce the overall cost of printing

Minimise your interventions — Replaceable Ink Pack System lets you print up to 40,000 ISO pages (black) without changing the ink packs⁴; up to 830 sheets total paper capacity⁵ with optional second paper tray

Fast print speed; no warm-up 24 ISO ppm (mono)[†]; zero second warm-up, fast first page out

Do more — 50-page duplex Auto Document Feeder; auto 2-sided print, copy, scan, email and fax

Open-platform ready – seamless integration with enterprise applications such as PaperCut MF

and other workflows; supports PCL¹ and PostScript 3

Security features – PIN number certification for job release; user control access; printer and network settings via Web Config with printer's IP address; SSL/TLS security; IPsec

Easy networking and administration — easy network setup designed for managed \mbox{IT} environments³

More time, less energy — uses up to 87 percent less power than laser printers⁶

Wired and wireless connectivity — includes Wi-Fi Direct^{®7}; print from

smartphones and tablets, including files from the cloud⁸

Designed for use exclusively with Epson® ink packs*.

lultifunction

Workgroup

EXCEED YOUR VISION

WorkForce® Pro WF-M5799 Replaceable Ink Pack System

Print

Printing Technology PrecisionCore 4S printhead single black inkiet

Printer Language Epson ESC/P®-R, PCL 5 emulation¹, PCL 6 emulation¹, PostScript 3 emulation

Maximum Print Resolution 4800 x 1200 optimized dpi ISO Print Speed[†] 24 ISO ppm (black)

Two-Sided ISO Print Speed⁺ 15 ISO ppm (black) Maximum Draft Print Speed⁺⁺ 34 ppm (black) Minimum Ink Droplet Size As small as 3.8 picoliters Duty Cycle⁹ Up to 45,000 pages (Recommended monthly page volume: up to 2,500 pages)

Mobile Printing

Epson Connect[™] Solutions[®] Epson Email Print, Epson iPrint[™] Mobile App, Epson Remote Print Other Apple[®] AirPrint[®], Google Cloud Print[™], Fire[™] OS

Copy

ISO Copy Speed*** 22 ISO cpm (black) Copy Quality Black-and-White: Standard/Best Copy Quantity 1-999 (PC-free) Maximum Copy Size 8.5" x 14' Copy Features Auto 2-sided, Preview, Resize, ID Copy, Collate, Adjustable Copy Density, Remove Punched Holes, Remove Shadows

Scan

Scanner Type colour flatbed/Auto 2-sided ADF Photoelectric Device colour CIS line sensor Scanbed Size 8.5" x 14" Optical Resolution 1200 dpi Hardware Resolution 1200 x 2400 dpi Maximum Resolution 9600 dpi interpolated Scanner Bit Depth 48-bit colour input/24-bit colour output Scan Features Scan to PC via Document Capture Pro, Scan to Cloud¹⁰ (including email), Memory Device, Scan to Network Folder, Password Protected PDFs

Fax

Black-and-white and colour Modem: 33.6 Kbps - as fast as 3 sec per page Memory: Up to 550 pages Speed Dials: 200 (max.) PC-Fax

Security

Security Features PIN number certification for job release, user control access; printer and network settings via Web Config using printer's IP address, SSL/TLS security, IPsec

Connectivity

Standard Connectivity

Hi-Speed USB (compatible with USB 2.0 specification) Wireless LAN IEEE (802.11 b/g/n) Wired Ethernet (1000 Base-T/100 Base-TX/10 Base-T)

Wi-Fi Direct7 Network Protocols TCP/IP v4/v6

Network Printing Protocols IPP, LDP, Port 9100, WSD Network Management Protocols SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, Ping, SLP, WSD, LLTD WLAN Security WEP 64 Bit, WEP 128 Bit, WPA PSK (AES)

Auto Document Feeder

50 sheets

Operating Systems

Windows® 10 (32-bit, 64-bit), Windows 8 (32-bit, 64-bit), Windows 7 (32-bit, 64-bit), Windows Vista® (32-bit, 64-bit), Windows XP SP3 (32-bit), Windows XP Professional x64 Edition, Windows Server 2012 R2¹¹, Windows Server 2012¹¹, Windows Server 2008 R2¹¹, Windows Server 2008¹¹, Windows Server 2003 R2¹¹, Windows Server 2003¹¹ Windows Server 2003 R2¹¹, Windows Server 2003¹¹ Mac® OS X® 10.5.8-10.13.x12 Mac OS X Server¹²

Solutions

Open Platform — compatible with third-party software

Paper Handling

PC-free Paper Support Plain (Letter, A4), Photo (Letter, A4,

Maximum Paper Size 8.5" x 47.2"

Paper Sizes 3.5" x 5", 4" x 6", 5" x 7", 8" x 10", 8.5" x 11", 8.5" x 14", A4, A6, half letter, executive, user definable (3" x 5"–8.5" x 47")

Paper Types Plain paper, Epson Bright White Paper, Epson Presentation Paper Matte, Epson Premium Presentation Paper Matte, Epson Premium Presentation Paper Matte Double-sided, Epson Photo Glossy, Epson Premium Photo Paper Glossy, Epson Ultra Premium Photo Paper Glossy, Epson Premium Photo Paper Semi-gloss

Envelope Types No. 10

Input Paper Capacity 830 sheets plain paper (250 sheets plain paper x 1 tray), 500 sheets plain paper optional tray, Rear feed: 80 sheets, 10 envelopes

General

Display 4.3" colour touchscreen Temperature Operating: 50 ° to 95 °F (10 ° to 35 °C) Storage: -4 ° to 104 °F (-20 ° to 40 °C) **Relative Humidity**

Operating: 20-80% Storage: 5-85% (no condensation)

*This product uses only genuine Epson-brand ink packs. Other brands of ink supplies are not compatible and, even if described as compatible, may not function properly.

+ Black print speeds are measured in accordance with ISO/IEC 24734. Actual print times will vary based on factors including system configuration, software, and page complexity. For more information, visit www.epson.com/printspeed i + Maximum To lack plint spects are measured in tactoriate for with North 2 21/97-2 data plint lines will vary based on factors including system configuration, software, and page complexity. If the Plack copy spects (cpm) are determined in detaut, single-side mode, in accordance with ISO/IEC 29183. Actual copy times will vary based on factors including system configuration and page complexity. Fir more information, visit www.epson.com/copyspect 11 Maximud Variance Vari 3 Epson Device Admin provides IT Managers the tools and resources to efficiently manage their fleed of printers and copiers I 4 Replacement ink pack yields are based on the ISO/IEC 24711 standard using the ISO/IEC 19752 pattern in Default Mode printing continuously. Ink pack yields vary considerably for reasons including images printed, print settings, temperature, humidity, and frequency of use. Yields may be lower when printing infrequently. Ink is used for printer startup and a variable amount of ink remains in the ink pack after the "replace ink pack" signal. For details, see www.epson.com/inkinfo I SW th optional second paper tray. I 6 Compared with 18 (eighteen) A4 single-function mono printers up to and including 35ppm in the Australian marketplace as at October 2018. The Epson WIF-M5299 uses, on average, up to 87% less energy when copying or printing. Actual power savings will vary by product model and usage. I 7W i-FI CERTIFIEDTM: level of performance subject to the range of the router being used. WI-FI Direct may require printer software. I 8 Most features require an Internet connection to the printer, as well as an Internet - and/or email-enabled evice. For a list of Epson Connect enabled printers and compatible devices and aps, visit www.epson.com/connect 19 Monthly duty cycle up to 45,000 is the highest duty a user could expect in a month, based on near-constant operation of a device of this kind. It is not recommended that the device be run at this duty. For best device performance, run the device at the recommended duty of 2,500 pages per month. I 10 Sender Supported cloud services, visit www.epson.com.u i 11 Only printing and scanning are supported under Windows Sure OS. It 25 compares are used with a lever cound expecting an printer device printer and expecting and printer device printer and use and used the supported under Windows Sure OS. It 25 compares are used to the expected with a user could expect in a month, based on near-constant operation of a device of this kind. It is not re and/or functions may not be supported under Mac OS X. | 13 Based on ENERGY STAR TEC measurement methodology; 288 prints/day, actual electricity consumption may vary depending on printer use. For more information, see www.energystar.gov storage conditions. Actual print stability will vary according to media, printed image, display conditions, light intensity, temperature, humidity and atmospheric conditions. Epson does not guarantee the longevity of prints. For maximum print life, display all prints under glass or UV filter or properly store them. I 16 For convenient and reasonable recycling options, visit www.epson.com.au I

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future eco.epson.com

Epson Australia

3 Talavera Road, North Ryde NSW 2113

Epson New Zealand

Level 2, 7-9 Franshawe Street, Auckland 1010

www.epson.com.au www.epson.co.nz

Specifications and terms are subject to change without notice. EPSON, Epson ESC/P, DURABrite, PrecisionCore and WorkForce are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future, Epson Connect and Epson iPrint are trademarks of Seiko Epson Corporation. AirPrint, Apple, Mac and OS X are trademarks of Apple Inc., registered in the U.S. and other countries. Google Cloud Print is a trademarks of Google LLC. Windows, Server and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Wi-Fi Direct® is a registered trademark and Wi-Fi CERTIFIED™ is a trademark of Wi-Fi Alliance®. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2018 Epson Australia 11/18

Specification Sheet | Page 2 of 2

General (continued)

Sound Level Power: 6.8 dB(A) Pressure: 54 dB(A) Rated Voltage AC 100–240 V Universal (Automatic) Rated Frequency 50–60 Hz Rated Current 0.9–0.5 A **Power Consumption** Copying/Printing: Approx. 23 W ISO 24712

Jultifunction

Workgroup

Standby: Approx. 10 W Sleep: Approx. 1.4 W Power Off: Approx. 0.2 W

ENERGY STAR® qualified Typical Energy Consumption (TEC)¹³ 0.2 kWh Safety Approvals Safety standards UL60950, CSA C22.2 No. 60950 EMI FCC Part 15 subpart B class B, CAN/CSA-CEI/IEC CISPR 22 class B

Country of Origin Indonesia

Weight and Dimensions (W x D x H) Printing: 425 x 535 x 357mm Weight: 18.3 kg Warranty 1-year on-site warranty

What's in the Box

Epson WorkForce Pro WF-M5799 multifunction printer, DURABrite® One initial ink pack: Black

Software Included¹⁴

Epson printer driver, PCL 5 driver emulation¹, PCL 6 driver emulation¹. PostScript 3 emulation. Document Capture Pro

Ink

Ink Type DURABrite Ultra pigment ink

Ink Palette Black

Ink Pack Configuration One individual ink pack Fade Resistance/Print Longevity¹⁵ Up to 118 years Replacement Ink Packs⁴ C13T957192 Black XL (Yield, ISO pages — Black: 10,000)

C13T958192 Black XXL (Yield, ISO pages — Black: 40,000) Printer is designed for use with Epson ink packs only, not third-party ink systems*.

Eco Features

Save up to 50% of your paper supply with auto 2-sided printing **ENERGY STAR qualified** RoHS compliant

Recyclable product¹⁶ Epson Australia is a Full Partner with Planet Ark

Ordering Information

Contact:

WorkForce Pro WF-M5799	C11CG04501
Maintenance Box	C13T671600
Optional Input Tray	C12C932871