



## **Epson TM-T88VI**

## Reliable, ultra-fast reciept printer with state of the art mobile connectivity

Connect to multiple devices simultaneously

Ultrafast print speed of up to 350 mm/s

Reliability you can count on

Easy printing from mobile devices

Print from web-based applications

Triple interface connectivity to future proof growing businesses

Industry leading four year warranty

## **Epson TM-T88VI**

Product Specifications			
PAPER		COLOUR	Black / White
PAPER SIZE	80 mm: $79.50 \pm 0.50$ (W) mm x dia 83.00 mm	INSTALLATION	Horizontally, wall hanging
	58 mm: $57.50 \pm 0.50$ (W) mm x dia 83.00 mm	INTERFACE CONNECTORS	D.K.D. function
FONTS & STYLES		HUMIDITY	Operation 10% - 90%
PRINT SPEED	350 mm/s	TEMPERATURE	Operation 5 °C - 45 °C, Storage -10 °C - 50 °C
PRINT SPEED (DEFAULT)	300 mm/s	STANDARD COMPLIANCE	
PRINTING FONT	Font A (default): 12 x 24	SAFETY APPROVALS	RCM: AS / NZS CISPR class A
	Font B: 9 x 17 (including 2-dot horizontal spacing)		Energy-saving: ENERGY STAR
COLUMN CAPACITY RECIEPT	80 mm: 42/48/56 columns	OTHER	
	58 mm: 30/36/40 columns	WARRANTY	48 months
CHARACTER SIZE	Font A: 1.41 x 3.39 (W x H mm)	WHAT'S IN THE BOX	
	Font B: 0.99 x 2.40 (W x H mm)		Connector cover
CHARACTER SET	95 Alphanumeric, 18 set International, 128 x 43 Graphic		Main unit
PRINTING CHARACTERS	Text (incl. Euro symbol), Graphics, Barcode		PS-180 & AC cable
INTERFACES			Paper spacer
CONNECTIVITY	Built-in USB, Built-in Ethernet (10/100Base-T/TX) +		Power switch cover
	UIB (Serial, Parallel, Powered USB)		Roll paper
	Bluetooth 2.1+EDR (dedicated model)		Setup guide
	Wireless (USB wireless dongle): OT-WL05 (802.11		Warranty document
	a/b/g/n) or OT-WL02 (802.11 b/g/n)	OPTIONAL ACCESSORIES	
	Beacon (using Bluetooth low energy): Beacon dongle	C32C845040	WH-10 (040) Wall hanging bracket
DATA DUESED	(Epson approved dongle: Laird model BT-820)	C32C890739	OT-WL02 (739): Wireless LAN Dongle, 2.4 GHz
DATA BUFFER DATA BUFFER	AE Distance A Lib colorateble	C32C814596	Power supply cover
	45 Bytes or 4 kb, selectable	CONFIG BUILDS	TM T00/// 0.44 D '// '
POWER POWER SUPPLY	PS-180, AC cable	C31CE94241	TM-T88VI-241 Built-in ethernet, USB, serial,
OPERATING VOLTAGE	24 V	004.050.40.40	dark grey
	= · ·	C31CE94243	TM-T88VI-243 Built-in ethernet, USB, parallel,
POWER CONSUMPTION	Operating: 27.6 W Stand by: 0.5 W	C21CF04E01	gark grey
GENERAL	Statiu by. U.J W	C31CE94581	TM-T88VI-581 Built-in ethernet, USB, BT-iOS
PRODUCT DIMENSIONS	145 x 195 x 148 mm (Width x Depth x Height)	COVER DI HE (ORTIONAL)	dark grey
PRODUCT DIMENSIONS PRODUCT WEIGHT	1.6 kg	COVER PLUS (OPTIONAL) 1YWT88VI	CoverDive the consider peak TM T00\/
FNODUCI WEIGHT	1.0 kg	I T VV I ÖÖV I	CoverPlus 1yr service pack TM-T88VI

## Better Products for a Better Future











Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

**EPSON AUSTRALIA** 

3 Talavera Road North Ryde NSW 2113 Tel: 1300 361 054 www.epson.com.au

**EPSON NEW ZEALAND** 

Level 2 7-9 Fanshawe Street Auckland, 1010 Tel: 088 237 766 www.epson.co.nz





